

UNITED STATES
DEPARTMENT OF THE INTERIORS
GEOLOGICAL SURVEYSUBMIT IN TRIPPLICATE
(Other instructions on re-
verse side)Form 9-331
Budget Bufile No. 42 00424

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

RECEIVED

JUN 29 1981

1. OIL ☐ GAS ☒ OTHER ☐
WELL ☐ WELL ☐

2. NAME OF OPERATOR

3. ADDRESS OF OPERATOR
ESTORIL PRODUCING CORPORATION4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface
11th FLOOR, VAUGHN BUILDING, MIDLAND, TX 79701 U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

760' FSL + 1980' FEL, Section 15

14. PERMIT NO.

15. ELEVATIONS (Show whether DT, RT, OR, etc.)

3428.6 GR

5. LEASE DESIGNATION AND SERIAL NO.

NM 13641

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

BELCO FEDERAL

9. WELL NO.

10. FIELD AND POOL, OR WILDCAT (Morrow)

Antelope Ridge (Strawn)

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASection 45
T-23S, R34E

12. COUNTY OR PARISH

LEA

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Casing & Liner Procedures

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

10/1/80 Ran 46 jts. 5½", 20#, S 95, R 3 flush jts casing w/FL4S Atlas Bradford;
Ran 1813' of 5½" liner to 13167, T.D. 13120. Set liner shoe at 13167
cemented with 125 sax Class "H" cement. Top of liner set at 11354'.

10/3/80 Tested liner to 3000#, for 1 hour, test OK.

ACCEPTED FOR RECORD
ROGER A. CHAPMAN

JUL 2 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Daniel J. Miller

TITLE

Agent for
Estoril Producing Corporation

DATE 6/19/81

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side