

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. L-4782	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL <input type="checkbox"/>	GAS WELL <input type="checkbox"/>	OTHER- Dry
Name of Operator Amoco Production Company		
Address of Operator P. O. Box 68 Hobbs, NM 88240		
Location of Well UNIT LETTER <u>G</u> <u>1980</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>14</u> TOWNSHIP <u>23-S</u> RANGE <u>33-E</u> NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name State IU
9. Well No. 1
10. Field and Pool, or Wildcat Wildcat Delaware
12. County Lea

15. Elevation (Show whether DF, RT, GR, etc.)
3624.9' GL

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JQB <input type="checkbox"/>	

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Plugged well per the following:

Set 100' (125 sacks) of Class C cement (with 2% CaCl) from 830'-730'.
Set 180 (430 sacks) of Class C cement (with 2% CaCl) from 430'-250'.
Set 250' (300 sacks) of Class C cement (with 2% CaCl) from 250'-50'.
Spotted a 20-sack cement surface plug. Installed P X A marker and cleaned location.

0+4-NMOCD, H 1-Hou 1-Susp 1-W. Stafford, Hou 1-LBG

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Benton Green TITLE Assist. Admin. Analyst DATE 2-23-81

APPROVED BY Oil & Gas Inspector TITLE OIL & GAS INSPECTOR DATE JUN 15 1981

CONDITIONS OF APPROVAL, IF ANY: