

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐

2. NAME OF OPERATOR

THE SUPERIOR OIL COMPANY

3. ADDRESS OF OPERATOR

P.O. Box 4500 The Woodlands, Texas 77380

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

1980' FSL & 1980' FWL

AT SURFACE: Sec. 30, T23S-R32E

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

Straight hole

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☐

ABANDON\* ☐

(other) Set casing

5. LEASE

NM - 14157

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Tresnor Federal

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 30, T23S-R32E

12. COUNTY OR PARISH

Ira

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3593.4 GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

11-4-81- Drilling ahead. TD 15,588'. MW - 12.1#. POH for logs.

11-6-81

11-7-81 Rigged up Schlumberger and logged. MW - 12.1#

11-8-81 RIH to 12,500'. Circ. & cond. hole to run 5-1/2" liner. MW - 12.1#

11-9-81 Ran 90 jts. of 5-1/2", 23#, N-80 LT & C liner. Set hanger top at 12,242'. BTM. 15,588'.

11-10-81 Cemented w/1128 sxs class "H". Bumped plugs w/drill mud. WOC 8 hrs.

11-11-81 Cleaned out & tested top of liner to 2000 psi - OK.

11-12-81 Circulated hole & ND BOP's.

11-13-81 Released rig @ 1800 hrs.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. Bannantine TITLE Reg. Group Mgr. DATE November 17, 1981

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF

APPROVAL IF ANY:

U.S. GEOLOGICAL SURVEY

POSWELL, NEW MEXICO

\*See Instructions on Reverse Side

CC: USGS (o+5), RG  
Hobbs (1)