

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYSUBMIT IN TRIPLICATE
(Other instructions on
reverse side)Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

NM 25465

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER

2. NAME OF OPERATOR

Sanders Petroleum Corporation

3. ADDRESS OF OPERATOR

11000-D Spain Rd. NE, Albuquerque, NM 87111

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*

See also space 17 below.)
At surface

660' FEL & 1650' FSL, Sec. 25, T23S, R33E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3632GL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Williamson Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR BLK. AND
SURVEY OR AREASec. 25, T23S, R33E,
NMPM

12. COUNTY OR PARISH

Lea

13. STATE

NM

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other) Run Casing & Cement

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-22-81. Current Depth 1330'. Set 8-5/8" 24# K-55 casing at 1330'. Cement with 200 sx. Class "C" thickset with 10# Gilsonite and 1/2# Flocele/sack; 250 sx. Howco-Lite with 2% CaCl, 1/4# Flocele, 5# Gilsonite/sk.; 200 sx. class "C" with 2% CaCl. Top of cement by temp. survey 520'.

7-23-81. Ran 1" pipe to 520', cemented stage #1 with 80 sx. Class "C", waited 2 hours, stage #2 with 50 sx., waited 3 hours, filled hole with water, held. Stage #3 with 270 sx., cement circ., circulated out 40 sx. (all stages contained 4% CaCl). Tested casing and BOP to 1200 psi before drilling out.

RECEIVED
JUL 29 1981U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Charles W. Sanders

TITLE President

DATE 7-27-81

(This space for Federal or State office use)

APPROVED BY
CONDITIONSACCEPTED FOR RECORD
ROBERT W. HARMAN

TITLE

DATE

JUL 29 1981

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side