

District I
PO Box 1980, Hobbs, NM 88241-1980
District II
PO Drawer DD, Artesia, NM 88211-0719
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
PO Box 2068, Santa Fe, NM 87504-2068

State of New Mexico
Energy, Minerals & Natural Resources Department

OIL CONSERVATION DIVISION
PO Box 2088
Santa Fe, NM 87504-2088

Form C-101
Revised February 10, 1994
Instructions on back
Submit to Appropriate District Office
State Lease - 6 Copies
Fee Lease - 5 Copies

☐ AMENDED REPORT

APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE

¹ Operator Name and Address. BTA Oil Producers 104 S. Pecos Midland, TX 79701		¹ OGRID Number 003002
		¹ API Number 30-025-27486
⁴ Property Code 002348	⁴ Property Name State 2, 8016 JV-P	⁴ Well No. 1

⁷ Surface Location

UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
N	2	23S	34E		660	South	1980	West	Lea

⁸ Proposed Bottom Hole Location If Different From Surface

UL or lot no.	Section	Township	Range	Lot Ida	Feet from the	North/South line	Feet from the	East/West line	County
⁹ Proposed Pool 1 Wildcat (Bone Springs)					⁹ Proposed Pool 2				

¹¹ Work Type Code	¹¹ Well Type Code	¹² Cable/Rotary	¹⁴ Lease Type Code	¹¹ Grossed Level Elevation
P	O	W/O	S	3408
¹¹ Multiple	¹¹ Proposed Depth	¹¹ Formation	¹¹ Contractor	¹¹ Spud Date
No	113380 TD 11337 PB	Bone Springs	N/A	1-30-95

EXISTING ~~XXXXXX~~ ¹³ Proposed Casing and Cement Program

Hole Size	Casing Size	Casing weight/foot	Setting Depth	Sacks of Cement	Estimated TOC
26"	20	94,106,133	1515	2450	Surface
17-1/2	13-3/8	54,61,68,72	4851	3000	3450
12-1/4	9-5/8	47, 53.5	11700	3600	DV @ 5516
	7-5/8	39	11387-12750	320	
	5	23.2	12550-13380	200	

¹³ Describe the proposed program. If this application is to DEEPEN or PLUG BACK give the data on the present productive zone and proposed new productive zone. Describe the blowout prevention program, if any. Use additional sheets if necessary.

Present: Perfs: 11926-11936

Proposed: ND Well head & install BOP, Release pkr & POH, GIH w/7-5/8" CIBP on 2-7/8" tbg. Set CIBP @ 11830' & spot 25 sx cmt on top. Spot 100' plug @ 11437' (50' below top of liner back to 50' above), Spot 300 gal 10% Ac Acid, Run GR-CCL from 8500-8000' Perf 8394'-8458' w/2 SPF, Swab & test to evaluate.

¹⁴ I hereby certify that the information given above is true and complete to the best of my knowledge and belief.

Signature:

Dorothy Houghton

Printed name:

Dorothy Houghton

Title:

Regulatory Administrator

Date:

1-20-95

Phone:

(915)682-3753

OIL CONSERVATION DIVISION

Approved by:

Gregory A. Sexton

Title:

DISTRICT I SUPERVISOR

Approval Date:

JAN 30 1995

Expiration Date:

Conditions of Approval:

Attached ☐

RECEIVED

JAN 26 1965

U.S. AIR FORCE
OFFICE