NO. OF COPIES RECEIVED		Form C-103
DISTRIBUTION		Supersedes Old
SANTA FE	NEW MEXICO OIL CONSERVATION COMMISSION	C-102 and C-103 Effective 1-1-65
FILE		
U.S.G.S.		Sa. Indicate Type of Lease
LAND OFFICE .		State X Fee
OFERA. CR		5. State Oil & Gas Lease No. NMB-1040
SUNDR	Y NOTICES AND REPORTS ON WELLS	W19-1040
(DO NOT USE THIS FORM FOR PRO- USE "APPLICAT)	Y NOTICES AND REPORTS ON WELLS POSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ON FOR PERMIT - "(FOAM C-101) FOR SUCH PROPOSALS.)	
OIL GAS X	OTHER•	7. Unit Agreement Name
2. Name of Operator BTA OIL PRODUCERS		8. Farm or Lease Name
3. Address of Operator		State 2, 8006 JV-P
104 South Pecos Midland, Texas 79701		9. Well No.
4. Location of Well	1411u, 16x43 /9/01	10. Field and Pool, or Wildcat
UNIT LETTER "N" 6	60 FEET FROM THE SOUTH LINE AND 1980 FEET FRO	Andalana Dalas (8)
THE West LINE, SECTIO	N 2 TOWNSHIP 23-S RANGE 34-E NMPN	
LINE, SECTION		
	15. Elevation (Show whether DF, RT, GR, etc.)	12. County
	Appropriate Box To Indicate Nature of Notice, Report or O	Lea ////////
PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER	PLUG AND ABANDON REMEDIAL WORK COMMENCE DRILLING DPNS. CHANGE PLANS CASING TEST AND CEMENT JQB X	T REPORT OF: ALTERING CASING PLUG AND ABANDONMENT
17. Describe Proposed or Completed Ope	erations (Clearly state all pertinent details, and give pertinent dates, includin	g estimated date of starting any propose
8/19/81 Cmtd 30" Conductor pipe @ 70 ' w/ 150 sx.		
8/30/81 Spudded @ 5:00 PM. Drlg 17월" hole in sand & surface rock.		
9/1/81 Reaming 17-½" hole to 26".		
9/12/81 Cmtd 20" 94, 106.5 & 133# csg @ 1515' w/2450 sx. Cmt circ. WOC.		
9/13/81 Tested csg to 1000 psi. Held OK. Drlg 17½" hole in anhydrite.		
11/1/81 Cmtd 13-3/8" 54.5, 61, 68 & 72# csg @ 4851' w/3000 sx. TOC @3450'. WOC.		
$11/2/81$ Tested csg to 1500 psi. Held OK. Drlg $12\frac{1}{2}$ " hole in lime and sand.		
11/30/81 Cmtd 9-5/8" 47 & 53.5# csg @ 11,700' w/3600 sx. DV Tool @ 5516'.		
12/3/81 Installed and tested BOP's. Tested DV Tool to 2500 psi. Held OK.		
12/4/81 Tested 9-5/8" csg to 2500 psi for 30 min. Held OK. Drlg 8½" hole in lime & shale.		
	above is true and complete to the best of my knowledge and belief.	(over)

THE Regulatory Administrator

2/9/82

17. (Continued)

- 12/24/81 Cmtd 7-5/8" 39# liner from 11,387' to 12,750' w/ 320 sx. WOC.
- 12/26/81 Tested liner to 2500 psi for 30 min. Held OK. Drlg 6½" hole in lime & shale.
- 1/15/82 Cmtd 5" 23.2 # liner from 12,550' to 13,380' w/ 200 sx. WOC.
- 1/16/82 Tested liner to 2000 psi for 30 min. Held OK.
- 1/24/82 Tested 5" & 7-5/8" liner, each under reduced hydrostatic = 10 ppg.
- 1/29/82 Removed BOP's & installed X-Mas tree. Perf'd Atoka, had 3600 psi. SITP. Set BP Valve.
- 1/30/82 Released rig @ 7:00 PM.

OFF ON WORLDANING DIA.

LEW 7 - 1885

BECEINED

PECEIVED

+ H.H. 1 2 JULY

UL DUNGEN DA DIN