

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐ other ☐
well well well
2. NAME OF OPERATOR
Estoril Producing Corporation
3. ADDRESS OF OPERATOR
11th Floor Vaughn Building
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980 FSL & 1980 FEL, Sec. 10
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐
Change casing program

5. LEASE
NM 15035
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Triple A Federal
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Wildcat (Bone Springs)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 10, T23S, R34E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3387.8 GR

RECEIVED
JAN 22 1982

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

OIL & GAS
U.S. GEOLOGICAL SURVEY
HOBBS, NEW MEXICO

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Run and set 83' of 20" conductor pipe. Set at 83', cement with 13 sacks of grout.

Run 17 jts. 16", 65#, H-40 csg. & set at 708', cement with 575 sacks Class "C" cement, 2% CaCl, 1/4# per sack Flowseal. **CIRCULATE**

Run 83 jts., 11 3/4 csg., set at 3281' and cement with 1600 sacks Halliburton Lite cement with 15# salt per sack, 1/4# per sack Floseal, and 300 Sacks Class "C" cement. **CIRCULATE**

Run 121 jts. 8 5/8" ST&C J-55 32# csg. and set at 4945' and cement with 650 sacks Halliburton Lite with 10# salt, 1/4# Floseal per sack, and 300 sacks Class "C" NEAT.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Production Clerk TITLE Production Clerk DATE 1-21-82

(This space for Federal or State office use)
(Orig. Sgd.) ROGER A. CHAPMAN
APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL: FEB 2 1982

FOR
JAMES A. GILLHAM
DISTRICT SUPERVISOR

*See Instructions on Reverse Side

RECEIVED

FEB 2 1962

NOTES 1/1/62