

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐ **WELL SERVICE**
ROSWELL, NEW MEXICO

2. NAME OF OPERATOR
TEXACO Inc.

3. ADDRESS OF OPERATOR
P. O. Box 728, Hobbs, New Mexico 88240

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 660' FNL & 1980' FWL
AT TOP PROD. INTERVAL: (Unit Letter 'C')
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

5. LEASE
LC-032104

6. IF INDIAN, ALLOTTEE OR TRIBE NAME
-

7. UNIT AGREEMENT NAME
-

8. FARM OR LEASE NAME
A.H. Blinebry Fed. NCT-3

9. WELL NO.
4

10. FIELD OR WILDCAT NAME
Drinkard

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 31, T-22-S, R-38-E

12. COUNTY OR PARISH
Lea

13. STATE
New Mexico

14. API NO.
3325' (GR)

15. ELEVATIONS (SHOW DF, KDB, AND WD)

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input checked="" type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>

(other) OF: Set & Cement 7" Csg.

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

TOTAL DEPTH 7650'
9 5/8" OD 32.3# H-40 Csg Set @ 1227'

1. Ran 7636' (201 Jts.) 7" OD 23#, 26#, 29# K-55 Csg & Set @ 7650'.
2. Cement 1st stage W/785 Sx. Class 'H' cement containing 5# gilsonite @ 1# flocele per sack.
3. W/DV Tool open @ 5026' cement 2nd stage W/660 sx. LW Cement containing 5# gilsonite & 1# flocele per sack. Cement circulated.
4. With DV Tool Open @ 2721' Cemented 3rd stage W/950 Sx. LW Cement Containing 15# salt per Sx. followed W/100 sx. Class 'C' Cement. Cement Circulated. Job Complete 2:15 PM, 9-23-82. WOC in excess of 18 hrs.
5. Tested 7" Csg to 1500# for 30 minutes, 5:15-5:45 PM, 9-29-82. Tested OK. Job Complete 5:45 PM, 9-29-82.

Subsurface Safety Valve: Manul. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] TITLE Asst. Dist. Mgr. DATE 9-30-82

APPROVED BY [Signature] TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD (This space for Federal or State office use)

OCT 7 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

See Instructions on Reverse Side