

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION  
P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-73

5a. Indicate Type of Lease  
State ☒ Fee ☐  
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☐ GAS WELL ☒ OTHER-  
Name of Operator  
AMOCO PRODUCTION COMPANY  
Address of Operator  
P. O. Box 68, Hobbs, NM 88240  
Location of Well  
UNIT LETTER N 660 FEET FROM THE South LINE AND 2030 FEET FROM  
THE West LINE, SECTION 11 TOWNSHIP 23 RANGE 34 NMPM.

7. Unit Agreement Name  
8. Farm or Lease Name  
State "ME"  
9. Well No.  
1-Y  
10. Field and Pool, or Wildcat  
Antelope Ridge Morrow

15. Elevation (Show whether DF, RT, GR, etc.)  
3388 RDB

12. County  
Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐  
TEMPORARILY ABANDON ☐  
PULL OR ALTER CASING ☐  
OTHER ☐  
PLUG AND ABANDON ☒  
CHANGE PLANS ☐  
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐  
COMMENCE DRILLING OPNS. ☐  
CASING TEST AND CEMENT JOBS ☐  
OTHER ☐  
ALTERING CASING ☐  
PLUG AND ABANDONMENT ☐

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Propose to PXA subject well. MI RUSU. Install BOP. POH with equipment. RIH with CIBP and set at 11900. Cap with 35' of class H cement. RIH with tbq and displace the wellbore with 820 bbls of 10# gelled brine. PU to 11520 and spot a 200' class H cement plug to 11320. (Top Wolfcamp 11418.) PU to 8593 and spot a 200' class H cement plug to 8393. (TOP of Bone Springs at 8493.) PU to 6393' and spot a 200' class H cement plug to 6193. PU to 4193 and spot a 200' class H cement plug to 3993. PU to 1993 and spot a 200' class H cement plug to 1793'. Spot a surface plug and cut off wellhead and install a dry hole marker.

MONET, S.S. OR BRASS OR MARKER

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

by S. Brownlee

TITLE Administrative Analyst

DATE 1-23-87

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

Approved by \_\_\_\_\_

TITLE \_\_\_\_\_

DATE 1-23-87

ADDITIONS OF APPROVAL, IF ANY:

**RECEIVED**  
JAN 26 1987  
OCD  
HOBBS OFFICE