

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen a well back to a present reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other

2. NAME OF OPERATOR

The Superior Oil Company

3. ADDRESS OF OPERATOR

P.O. Box 3901, Midland, Texas 79702

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 660' FSL & 1980' FWL of Sec. 11

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH: Straight Hole.

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

CHANGE ZONES ☒

ABANDON* ☐

(other) Plug back to Delaware

5. LEASE

NM - 19620

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Triste Draw Federal Gulf

9. WELL NO.

1

10. FIELD OR WILDCAT NAME

Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 11, T23S, R32E.

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)

3728

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Proposed procedure as recommended by Mr. Armando Lopez per telephone conversation 6-24-83, to abandon the Atoka Zone.

Est. start date 6-25-83

1. Set CIBP @ 14,209' in 2 3/8" tbg. pup joint below permanent packer @ 14,200. Test plug to 1000 psi.

2. Dump 3 sacks of sand on top of packer @ 14,200.

(Over)

Subsurface Safety Valve: Manu. and Type

Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED

G. E. Tate

TITLE Div. Opr. Supt.

DATE

6-28-83

APPROVED

(This space for Federal or State office use)

APPROVED BY *Sgt. PETER W. CHESTER*

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUL 7 1983

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1976 O - 214-149

3. Set 5", 18#, CIBP @ 14,100'. Test plug to 1000 psi. Cement plug on top of CIBP.
4. Set 7 5/8", 39#, CIBP @ 12,200'. Test plug to 1000 psi. Cement plug on top of CIBP.
5. Set 8 1/2", 39#, CIBP @ 8550' with 3 JH's. Set cement retainer and squeeze with 65 sacks Class H cement.

RECEIVED
O.C.D.
HOBBBS OFFICE