

UNITED STATES HOBBS, NEW MEXICO 88240

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ gas ☒ other ☐
2. NAME OF OPERATOR
The Superior Oil Company
3. ADDRESS OF OPERATOR
P. O. Box 4500, The Woodlands, TX 77380
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 2480' FEL of Sec. 14
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH: Straight hole


16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) Spudding & Casing Setting ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☐
☐
☐



OIL & GAS
U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

5. LEASE
NM - 11967
6. IF INDIAN, ALLOTTEE OR TRIBE NAME
7. UNIT AGREEMENT NAME
8. FARM OR LEASE NAME
Triste Draw Federal
9. WELL NO.
2
10. FIELD OR WILDCAT NAME
Wildcat
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 14 - T23S - R32E
12. COUNTY OR PARISH
Lea
13. STATE
New Mexico
14. API NO.
15. ELEVATIONS (SHOW DF, KDB, AND WD)
3705.7 GR

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Drove 30" conductor to 40'. Spudded in @1000 hrs.
1-12-82 Drilling ahead. (MD - 390') MW - 8.9#.
1-14-82 Drilling ahead. Prep. to run 16" csg.
(MD - 670') MW - 9.0#.
1-15-82 Set 16", 65# csg. @ 680'. Cement w/500 sxs class C to surface.
WOC. (MD - 680') MW - 9.0#.
1-16-82 NU BOP. Tested hydrill & csg. to 1000# @ 1000 hrs.- OK. Drilling ahead. (MD - 975') MW - 9.9#
1-17-82 thru 1-22-82 Drilling ahead. (MD - 3850') MW - 9.3#

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED G. Bannantine TITLE Regulatory Grp. Mgr DATE 1-22-82
G. Bannantine

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL FOR FEDERAL

ROGER A. CHAPMAN

FEB 5 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side