

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and productivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depth. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 30 through 34 shall be repeated for each zone. The form is to be filed in quadruplicate except on state land, where six copies are required. See Rule 1165.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kitland-Fruitland	T. Penn. "C"
U. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Delaware 5020'	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Quartz
T. Cloriet	T. McKee	Base Greenhorn	T. Granite
T. Bone Springs 8491'	T. Ellenburger	T. Dakota	T.
T. Blinbry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 8501' to 9000'	No. 4, from _____ to _____
No. 2, from 10,450' to 10,620'	No. 5, from _____ to _____
No. 3, from 10,660' to 10,832'	No. 6, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
No. 2, from _____ to _____ feet
No. 3, from _____ to _____ feet
No. 4, from _____ to _____ feet

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	10'	10'	Caliche				
10	650	640'	unconsolidated sand				
640	1780	1140'	Anhy & shale w/ lime stringers				
1780	5020	3240'	Anhy and salt section				
5020	8540	3520'	Redd Canyon Cherry Canyon Brushy Head sand stringers between lime stringers				
8520	709 10832	2312'	Carbonate w/ occasional sand stringers				

RECEIVED

JAN 22 1985

6-12
HODGE