

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

P.O. BOX 200  
ROSWELL, NEW MEXICO 80200

Form Approved.  
Budget Bureau No. 42-R1424

**SUNDRY NOTICES AND REPORTS ON WELLS**

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
ESTORIL PRODUCING CORPORATION

3. ADDRESS OF OPERATOR  
11th Floor, Vaughn Bldg., Midland, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Sec. 10, 660' FSL & 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐  
FRACTURE TREAT ☐  
SHOOT OR ACIDIZE ☐  
REPAIR WELL ☐  
PULL OR ALTER CASING ☐  
MULTIPLE COMPLETE ☐  
CHANGE ZONES ☐  
ABANDON\* ☐

(other) Perforate

SUBSEQUENT REPORT OF:

☐  
☐  
☐  
☐  
☐  
☐  
☐  
☒

5. LEASE  
NM 13838  
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ALTA FEDERAL

9. WELL NO.

ONE

10. FIELD OR WILDCAT NAME

UNDESIGNATED BONES SPRINGS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T20S, R34E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)  
3389.9' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

9-23-82 Ran Radioactive Tracer Survey, survey indicated channeling from 6752'-6920', & minor channeling from 6752-6758', 6830'-6920'.

9-24-82 Perforated 5½" csg @ 6375' w/ 4 shots for squeeze.

9-25-82 Ran Radioactive Tracer Survey, cemented 5½" csg through tbq & cmt retainer w/ 600 sx of class 'C' cmt & .5 of 1½ CFR<sub>2</sub>.

9-26-82 Ran WL Temp Survey.

Subsurface Safety Valve: Manu. and Type

Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kris Bar-tosh

TITLE Prod. Clerk

DATE 10-8-82

ACCEPTED FOR RECORD

(This space for Federal or State office use)

PETER W. CHESTER

APPROVED BY

CONDITIONS OF APPROVAL OF SEP 29 1983

TITLE

DATE

\*See Instructions on Reverse Side

RECEIVED

OCT 12 1982

OIL & GAS  
MINERALS REVENUE SERVICE  
ROSWELL, NEW MEXICO

RECEIVED  
OCT 3 1983  
O.C.D.  
HOBBS OFFICE

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR  
ESTORIL PRODUCING CORPORATION

3. ADDRESS OF OPERATOR  
11th Floor, Vaughn Bldg., Midland, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: Sec. 10, 660' FSL & 1980' FWL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT OF:
TEST WATER SHUT-OFF <input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT <input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE <input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL <input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE <input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES <input type="checkbox"/>	<input type="checkbox"/>
ABANDON* <input type="checkbox"/>	<input type="checkbox"/>
(other) Perforate	X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

- 9-28-82 Perforated 5½" csg w/ 1 shot per foot from 6329'-6344', acidized perforations from 6329'-6344' w/ 2000 gal of 7.5% NeFe acid & 24 ball sealers.
- 9-29-82 Ran Radiocative Tracer Survey, survey indicated slight channelling up to 6312', slight channelling dwn to 6352'.
- 10-1-82 Fraced perforations from 6329'-6344' w/ 5000 gallons of gelled wtr pad & 9000 gallons of gelled wtr w/ 1000 lbs of 20-40 sand & 1400 lbs of 10-20 sand.

Subsurface Safety Valve: Manu. and Type \_\_\_\_\_ Set @ \_\_\_\_\_ Ft.

18. I hereby certify that the foregoing is true and correct


SIGNED Kris Barten TITLE Prod. Clerk DATE 10-8-82

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

TITLE \_\_\_\_\_

DATE \_\_\_\_\_



OCT 12 1982

\*See Instructions on Reverse Side

CL & CAG  
MINERAL & WATER COMPLEX  
ROSWELL, NEW MEXICO

RECEIVED  
OCT 3 1983  
C.C.D.  
HOBBS OFFICE