

UNITED STATES M. OIL CONS. COMMISSION
P. O. BOX 1980
DEPARTMENT OF THE INTERIOR
HOBBS, NEW MEXICO 88240
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ well gas ☐ well other ☐

2. NAME OF OPERATOR
ESTORIL PRODUCING CORPORATION

3. ADDRESS OF OPERATOR
11th Floor, Vaughn Bldg., Midland, Tx

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: Sec. 10, 660' FSL & 1980' FWL
AT TOP PROD. INTERVAL:
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF	<input type="checkbox"/>	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	<input checked="" type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>	<input type="checkbox"/>
MULTIPLE COMPLETE	<input type="checkbox"/>	<input type="checkbox"/>
CHANGE ZONES	<input type="checkbox"/>	<input type="checkbox"/>
ABANDON*	<input type="checkbox"/>	<input type="checkbox"/>
(other)	<input type="checkbox"/>	<input type="checkbox"/>

5. LEASE

NM 13838

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

ALTA FEDERAL

9. WELL NO.

ONE

10. FIELD OR WILDCAT NAME

UNDESIGNATED BONES SPRINGS

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Sec. 10, T20S, R34E

12. COUNTY OR PARISH

LEA

13. STATE

NM

14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3389.9' GL

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

9-9-82 Fractured perforations 6768'-6772', 6778'-6788', 6802'-6830' w/ 20,000 gallons gelled 2% KCl fresh water & 3000 lbs. of 20-40 sand & 16500 lbs. of 10-20 sand, using rock salt for block, dropped block in 2 stages.

9-11-82 Laid 112- 2 3/8" tubing.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Kris Lartich TITLE Clerk DATE _____

ACCEPTED FOR RECORD

(This space for Federal or State office use)

ORIG. SGD.) DAVID R. GLASS

APPROVED BY _____ DATE _____

CONDITIONS OF APPROVAL IF ANY

OCT 8 1982

U.S. GEOLOGICAL SURVEY
ROSWELL, NEW MEXICO

*See Instructions on Reverse Side