N. M. OIL CONS. CO' SSIDN P. O. BOX 1980 HOBBS, NEW MEXICO 88240

Form 9-331 Dec. 1973

.

ومانججه

. •••

.

· · · ·

.

.

Form Approved.	
Budget Bureau No.	42-R1424

.

UNITED STATES	5. LEASE
DEPARTMENT OF THE INTERIOR	NM-19143
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different	7. UNIT AGREEMENT NAME
reservoir. Use Form 9–331–C for such proposals.)	8. FARM OR LEASE NAME Federal CW Com
1. oil gas 🕅 other	9. WELL NO.
2. NAME OF OPERATOR	
Amoco Production Company	Antelope Ridge Atoka
3. ADDRESS OF OPERATOR P. O. Box 68, Hobbs, New Mexico 88240	Antelope Ridge Morrow 11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
below.) AT SURFACE: 990' FEL X 660' FSL	3-23-34 12. COUNTY OR PARISHI 13. STATE
AT SURFACE: AT TOP PROD. INTERVAL: (Unit P, SE/4,SE/4)	Lea NM
AT TOTAL DEPTH:	14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3376.6' GL
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF:	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
PULL OR ALTER CASING MAR 18	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
	1503
	•
ABANDON* set casing MineRals MGMT	Contro DE
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly sta including estimated date of starting any proposed work. If well is measured and true vertical depths for all markers and zones pertine	ite all pertinent details, and give pertinent dates, directionally drilled, give subsurface locations and
On 3-7-83, 13-3/8" 61#, 68#, and 72# S-80 c DV tool at 2019'. Cemented casing with 400 450 sx class C lite, 400 sx class C and add DV tool and circulated. Cemented second st 400 sx class C with additives. Circulated 18 hrs. Pressure tested casing at 1000 psi and tag plug at 3904'. Tested casing at 10 to 12-1/4" and resumed drilling.	itives. Plugged down. Opened age with 1550 sx class C lite and 611 sx to pit. Plugged down. WOC for 30 min-OK. Drilled DV tool
0+6-BLM, R 1-HOU 1-W. Stafford, HOU 1	-CMH 1-Belco
Subsurface Safety Valve: Manu. and Type	Set @ Ft.
18. I heropy deryify that the foregoing is true and correct	_
18. I hereby remarks that the foregoing is true and correct	alvst 3-14-83
SIGNED Hacks M. Herring TITLE Ast. Adm. Ar	
ACCEPTED FOR RECORD STATE	office use)
APPROVED BY (ORIG. SGD.) DAVID R. GUASS	DATE
ACCEPTED FOR RECORD APPROVED BY <u>(ORIG. SGD.) DAVID R. GUAGS</u> CONDITIONS OF APPROVAL, IF ANY: MAR 2 2 1983	
MINERALS MANAGEMENT SERVICE	
ROSWELL, NEW MEXICO See Instructions on Rever	se Stud

•

ويتبو مردو

ARCHINED MAR & 3 1983 O.C.D. MORRE OFFICE

4