

DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☒ gas well ☐ other ☐2. NAME OF OPERATOR
Nortex Gas & Oil Company3. ADDRESS OF OPERATOR
403 Wall Towers West, Midland TX 79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)

AT SURFACE: 1980' FNL & 1980' FWL

AT TOP PROD. INTERVAL:

AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) ☐

SUBSEQUENT REPORT OF:

☐
☐
☐
☐
☐
☐
☐
☒

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

7-28-83 Spud @ 6:30 pm.

7-29-83 Set 8 5/8", 24#, K-55, ST&C casing @ 397'. Cemented w/220 sx C1 "C" + 2% CaCl. Circ. cmt. to surf.

8-4-83 Ran DST #1 - 5060'-5104'.

8-5-83 Ran DST #2 - 5159'-5165'.

8-6-83 TD 5295'. Ran logs.

8-7-83 TD 5295'. Set cement plugs in 7 7/8" hole as follows; 30 sx @ 5080'-4980'; 45 sx @ 1310'-1210'; 35 sx @ 347'-447'; 15 sx @ surface. Well P&A'd 8-7-83.

Weld on permanent well marker. Will clean pits soon as possible.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED L. W. Helms, Jr. TITLE Petroleum Engineer DATE 8-17-83

(This space for Federal or State office use)

APPROVED BY J. Frank Haden TITLE AREA MANAGER DATE 6-10-85
CONDITIONS OF APPROVAL, IF ANY:

Well Record 97