

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.O.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Samedan Oil Corporation 3. Address of Operator 600 N. Marienfeld, Suite 320, Midland, Texas, 79701 4. Location of Well UNIT LETTER <u>K</u> <u>2130</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM THE <u>West</u> LINE, SECTION <u>14</u> TOWNSHIP <u>22-S</u> RANGE <u>37-E</u> NMPM. 15. Elevation (Show whether DP, RT, GR, etc.) 3337.1 GR	7. Unit Agreement Name 8. Firm or Lease Name Parks "A" 9. Well No. 10 10. Field and Pool, or Wildcat Wantz (Abo/Granite Wash) 12. County Lea
--	--

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

1-7-84 RU csg tools & ran 5½" float shoe & float collar on 188 jts 5½"
15.5 J-55 ST&C csg & set @ 7480'. Circ ½ hr. Cemented 1st stage
w/170 sx Pacesetter Lite w/ 1#/sk HiSeal followed by 375 sx Class
"H" w/ 3/4% CF-1. Plug down @ 7:45 p.m. 1-8-84. Float held. Perf
4 .38 holes @ 4650'. Circ 7 hrs (no cmt). Cement 2nd stage w/950
sx Southwest Lite w/¼# celloseal followed by 300 sx Class "C".
Displace wiper plug to 4620'. SI head. Plug down @ 4:10 a.m.
1-9-84.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Division Clerk DATE 1-30-84

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY [Signature] TITLE [Signature] DATE FEB 1 1984

CONDITIONS OF APPROVAL, IF ANY: