Form Approved. Budget Bureau No. 42-R1424

New Mexico

## STATES DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY

5.	LEASE				
	NM	13641	A company		

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

Antelope Ridge - Cherry Canyon 11. SEC., T., R., M., OR BLK. AND SURVEY OR

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME APD Federal

10. FIELD OR WILDCAT NAME

Lea L

Sec 10, T-23-S, R-34-E

12. COUNT FOR PARISH 13. STATE

30-025-28554

15. ELEVATIONS (SHOW DF, KDB, AND WD) KB 3403, DF 3402, GL 3387

(NOTE: Report results of multiple completion or zone

9. WELL NO.

14. API NO.

SUNDRY	NOTICES.	AND	REPORTS	ON	WELLS
SUNDAL	INDITIOES	HIND	KEFUKIS	C.P. W	VV - 1 1 2

					4 A MW EN ET ET CO.
Do not use this form for proposals eservoir. Use Form 9–331–C for suc	to drii! h propo	or to desais.)	eepen or	plug back	to a different

1. oil well	gas well		other	Dry 1	Hole 🗝	James C.	
2. NAME O	F OPERA	TOR					
Belo	o Deve	1opmer	it Cor	porati	<b>i</b> on		
3. ADDRES	S OF OPE	ERATOR	One P	etrole	eum Cer	iter,	
Building	, 6, Su	ite 20	)l Mi	dland,	, Texas	79705	
4. LOCATIO below.)	N OF WE	LL (REPO	ORT LOC	ATION (	CLEARLY.	See space :	17

990' FSL & 1940' FEL AT SURFACE:

AT TOP PROD. INTERVAL: AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL
TEST WATER SHUT-OFF
FRACTURE TREAT
SHOOT OR ACIDIZE
REPAIR WELL
PULL OR ALTER CASING
MULTIPLE COMPLETE
CHANGE ZONES
ABANDON*
(other)

SUBSEQUENT REPORT OF:

change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Prep to P & A. Received verbal approval from BLM to P & A 2-9-84. Spot 40 sx Class "H" cement from 4970-4870". Out 7-5/8" casing @ 3310". POH  $\rm w/3310'$  of 7-5/8" casing. Spot 50 sx Glass "H" cement  $\rm w/3\%$  CaCl2 from 3360-3250'. WOC 5 hrs. Tag cement plug with wireline @ 3250'. Spot 10 sx Class "H" cement 0 surface. Weld steel plate on top of cutoff. Frect dry hole marker. Well P & A'd 2-11-84.

Subsurface Safety Volve: Manu. and Type	
18. Thereby certify that the foregoing is true and correct	
SIGNED COLOR L. W. Helms, Jrms Drill:	ing Engineer DATE 11-13-84
Che . 6 de . (This space for Feder	al or State office use)
APPROVED BY TITLE	DATE 4-10-84