

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	7. Unit Agreement Name
2. Name of Operator Samedan Oil Corporation	8. Farm or Lease Name Parks "A"
3. Address of Operator 600 N. Marienfeld, Suite 320, Midland, Texas, 79701	9. Well No. 12
4. Location of Well UNIT LETTER I, 2310 FEET FROM THE South LINE AND 330 FEET FROM East THE LINE, SECTION 14 TOWNSHIP 22-S RANGE 37-E NMPM.	10. Field and Pool, or Wildcat Wantz Abo & Granite Wash
15. Elevation (Show whether DF, RT, GR, etc.) 3330.1	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work; SEE RULE 1103.

5-8-84 Spud 14-3/4" hole @ 2:45 p.m. (5-8-84).

5-10-84 TD 14-3/4" hole @ 2:00 p.m. Ran 10-3/4 regular guide shoe and float collar and 5 centralizers and 26 jts 10-3/4" 32.75# H-40 ST&C. Set @ 1090'. Cemented w/460 sx Howco Lite w/3% salt + 1/4# flocele. Tail in w/250 sx Class "C" w/2% cc. Circulate 100 sx to pit. Plug down @ 7:10 p.m. Float held. WOC 9-1/4 hrs. Test csg to 1000# f/ 30 minutes.

*Min WOC
13 HRS*

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED *V. J. Diamond* TITLE Division Clerk DATE 6/4/84

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

JUN 6 1984

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

JUN 5 1984

O.C.D. [illegible]
HOBBS OFFICE