

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. UNIT AGREEMENT NAME
2. NAME OF OPERATOR TEXACO INC	8. FARM OR LEASE NAME A.H. BLINEBRY FED. NCT-1
3. ADDRESS OF OPERATOR P.O. BOX 728; HOBBS, NEW MEXICO	9. WELL NO. 42
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface UNIT LETTER K, 1980' FSL & 1980' FWL	10. FIELD AND POOL, OR WILDCAT SOUTH BRUNSON DRINKARD ABO
14. PERMIT NO. 30-025-28823	15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3361.6 K-B.
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SECT 33 T-22S R-38E
	12. COUNTY OR PARISH LEA.
	18. STATE NEW MEXICO

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other) Open additional pay

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. MIRU. PULL RODS AND PUMP. TOH W/ PRODUCTION TBG.

2. SET RETRIEVABLE BRIDGE PLUG AT 6720' (PERFS 6790'-7311')

3. PERFORATE UPPER SOUTH BRUNSON DRINKARD ABO POOL AT 6450'-57', 97'-98', 6528'-30', 51'-57', 61'-64', 68'-71', 84'-85', 90'-91', 6600'-04', 14', 27', 40', 58'-59', AND 6678'-79'. 44 INTERVALS, 25 PE, 88 SHOTS

4. TIH W/ PACKER AND TEST WORKING TO 5000 PSI. SET PACKER AT 6300'.

5. ACIDIZE SOUTH BRUNSON DRINKARD ABO PERFORATIONS (6450'-6679') W/ 5000 GALLONS 15% NEFE HCL. 3 BPM, MAX PRESSURE OF 4000 PSI. DROP 100 BALL SEALERS.

6. SWAB OR FLOW LOAD BACK.

7. GELLED ACID FRACTURE SOUTH BRUNSON DRINKARD ABO PERFORATIONS WITH 24000 GALLONS 20% GELLED NEFE ACID, 24,000 GALLONS 40% GELLED PAD WITH 18,000 LBS OF 100 MESH SAND, 15 BPM, MAX PRESSURE 4000 PSI.

8. SWAB OR FLOW LOAD BACK. TOH

9. TIH AND RETRIEVE B.P. TOH

10. TIH WITH PRODUCTION EQUIPMENT

11. TEST AND SUBMIT TO N.M.O.C.D. FOR ALLOWABLE.

(TOP OF SOUTH BRUNSON DRINKARD ABO 6442)

18. I hereby certify that the foregoing is true and correct

SIGNED KL Johnson

TITLE AREA SUPERINTENDENT

DATE APR 28 1988

(This space for Federal or State office use)

APPROVED BY PAUL GRI

TITLE

DATE 5 9 88

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

RECEIVED

MAY 12 1988

STO
H-1000-01102