

MAX GUIMAN #9
Sec.19,T.22S,R.38E
Iea County, New Mexico

Perforation Record, Acid, Shot, Fracture, Cement Squeeze, Etc.:

Granite Wash Formation - Plugged & Abandoned:

Perf 7624-7653' (10 holes) - Acidized w/2,000 gals 15% Acid	11/30/84
Perf 7584-7608' (9 holes) - Acidized w/3,000 gals 15% Acid	11/30/84
Perf 7552-7568' (9 holes) - Acidized w/3,000 gals 15% Acid	11/30/84
Perf 7376-7424' (15 holes) - Acidized w/5,000 gals 15% Acid	12/17/84
Squeezed w/100 sx Type "H" cement to 2100# (7624-7568').	01/28/85
Squeezed w/200 sx Type "H" cement to 4500# (7376-7424').	01/28/85
Perf 7324-7348' (13 holes) - Acidized w/1,500 gals 15% FE Acid.	02/05/85
Ran CIBP & set @ 7318'. 2-5-85	

Drinkard Formation - Temporarily Abandoned:

Perf 7093-7301' (17 holes) - Acidized w/5,000 gals 15% NE Acid	02/06/85
Frac w/40,000 gals gel wtr & 22,000# 20/40 sand	
Perf 6813-6897' (17 holes) - Acidized w/3,500 gals 15% NE Acid	02/08/85
Perf 6462-6596' (20 holes) - Acidized w/3,500 gals 15% NE Acid	
Frac w/40,000 gals gel wtr & 46,000# 20/40 sand	02/11/85
Set RBP @ 6062' to temporarily abandon.	

Blinebry Formation:

Lower Blinebry -

Perf 5868-5986' (16 holes) - Acidized w/3,000 gals 15% NE Acid	03/12/85
Frac w/50,000 gals gel wtr & 90,000# 20/40 sand	

Middle Blinebry -

Perf 5598-5700' (20 holes) - Acidized w/3,000 gals 15% NE Acid	03/15/85
Frac w/50,000 gals gel wtr & 90,000# 20/40 sand	

7