

NEW MEXICO OIL CONSERVATION COMMISSION
WELL COMPLETION OR RECOMPLETION REPORT AND LOGPlease hold confidential as long as law allows.
7/17/845a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-229

7. Unit Agreement Name

8. Farm or Lease Name

J. F. Janda (NCT-J)

9. Well No.

5

10. Field and Pool, or Wildcat

Jalmat (Oil)

12. County

Lea

19. Elev. Casinghead

3487

25. Was Directional Survey Made

No

27. Was Well Cored

No

CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
9-5/8	40	423	12-1/4	300 sx (circ)	none
7	26	3900	8-3/4	1350 sx (circ)	none

LINER RECORD					TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN	SIZE	DEPTH SET	PACKER SET
					2-3/8	3828	none

31. Perforation Record (Interval, size and number)				32. ACID, SHOT, FRACTURE, CEMENT SQUEEZE, ETC.		
22 shots with one shot each at: 3202, 3208, 3211, 3214, 3217, 3239, 3243, 3247, 3253, 3256, 3259, 3275, 3279, 3282, 3590, 3592, 3610, 3639, 3643, 3671, 3690, 3692				DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	
				3202-3692	A/5500	15% MCA

33. PRODUCTION							
Date First Production		Production Method (Flowing, gas lift, pumping - Size and type pump)				Well Status (Prod. or Shut-in)	
12-06-84		Pumping (11 x 64 x 1-1/4)				Producing	
Date of Test	Hours Tested	Choke Size	Prod'n. For Test Period	Oil - Bbl.	Gas - MCF	Water - Bbl.	Gas - Oil Ratio
12-08-84	24	14/64		7	24	7	3429
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl.	Gas - MCF	Water - Bbl.	Oil Gravity - API (Corr.)	
-----	21 psi		7	24	7	34	

34. Disposition of Gas (Sold, used for fuel, vented, etc.)						Test Witnessed By
Vented						Harold Swain

35. List of Attachments	
C-104, Inclination Report, Logs	

36. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief.

SIGNED Larry A. Nimmer TITLE Engineer DATE December 14, 1984

This form is to be filed with the appropriate District Office of the Commission not later than 30 days after the completion of the well. It shall be accompanied by a copy of all electrical and radioactivity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of sectionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

Janda J No. 5

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy 1285	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt 1404	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt 3035	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 3193	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3390	T. Devonian	T. Menefee	T. Madison
T. Queen 3820	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinberry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand	T. Entrada	T.
T. Abo	T. Bone Springs	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn.	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from 3202 to 3692	No. 4, from to
No. 2, from to	No. 5, from to
No. 3, from to	No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet	
No. 2, from to feet	
No. 3, from to feet	
No. 4, from to feet	

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
1285	1404	119	Anhydrite				
1404	3035	1631	Salt and Anhydrite				
3035	3193	158	Dolomite and Anhydrite				
3193	3390	197	Sandstone and Dolomite				
3390	3820	430	Sandstone and Dolomite				
3820	3900	80	Sandstone and Dolomite				