

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
HOBBS, NEW MEXICO 88240

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	5. LEASE DESIGNATION AND SERIAL NO. NM 38469
2. NAME OF OPERATOR Yates Petroleum Corporation	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR 207 South 4th St., Artesia, NM 88210	7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 330 FSL & 1650 FEL, Sec. 30-T23S-R34E	8. FARM OR LEASE NAME Kestrel ABE Federal
	9. WELL NO. 1
	10. FIELD AND POOL, OR WILDCAT Und. Bell Lake Bone Springs
	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Unit 0, Sec. 30-T23S-R34E
14. PERMIT NO.	15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3629' GR
	12. COUNTY OR PARISH Lea
	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETE

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON\*

SHOOTING OR ACIDIZING

ABANDONMENT\*

REPAIR WELL

CHANGE PLANS

(Other) Correction on perms

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

CORRECTION:\*

4-10-85. Reperforated\*8712-82' w/14 .42" holes. Acidized perms\*8712-82' w/3000 gals 15% Spearhead acid and 35 ball sealers.

4-16-85. Acidized (via 5 1/2" casing) perms\*8712-82' w/21000 gals Retarded acid as follows:  
1000 gals 15% DS-30 acid, 5000 gals Pad, 9000 gals 20% acid. 400# Benzoic acid flake block, 1000 gals 20% acid, 5000 gals Pad, 10000 gals acid, 304 bbls flush.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Production Supervisor

DATE

5-30-85

(This space for Federal or State office use)

APPROVED BY/ACCEPTED FOR RECORD

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

JUN 4 1985

\*See Instructions on Reverse Side

RECEIVED

JUN - 5 1989

O.C.C.  
HOBBS OFFICE