

N. M. OIL CONS. COMMISSION

~~U.S. DEPARTMENT OF THE INTERIOR~~ 1980

HOBBS, NEW MEXICO 88240

Form Approved.
Budget Bureau No. 42-R1424

Form 9-331
Dec. 1973

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☐ well gas ☒ well other ☐

2. NAME OF OPERATOR
Santa Fe Energy Company

3. ADDRESS OF OPERATOR
500 W. Illinois, Suite 500, Midland, TX79701

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FWL & 660' FSL
AT TOP PROD. INTERVAL: same
AT TOTAL DEPTH: same

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☐
(other) set casing

☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
~~NM 26390~~ NM 63994

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Platinum 6 Federal

9. WELL NO.
1

10. FIELD OR WILDCAT NAME
Wildcat

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
6, T23S, R32E

12. COUNTY OR PARISH
Lea

13. STATE
NM

14. API NO.
30-025-29361

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3517.3'

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*
9-23-85: Hole size 12-1/4". Ran 10-3/4", 60# S-95 Buttress and 55.5# S-95 Buttress to 4550'. Cement with 2350 sx Thriftyment with 5# salt/sx. Slurry weight 11.5, volume 1180 + 670 sx Class "C" neet (no additives) 14.8# slurry weight, 157.5 volume. Circ 175 sx to pit.

WOC 34 hours. Test casing to 3000 psi.

Subsurface Safety Valve: Manu. and Type n/a Set @ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Michael R. Bunter TITLE Sr. Drig Engr. DATE 10-15-85

(This space for Federal or State office use)

APPROVED BY ACCEPTED FOR RECORD
CONDITIONS OF APPROVAL IF ANY

TITLE DATE

OCT 21 1985

*See Instructions on Reverse Side

CARISBAD, NEW MEXICO

RECEIVED
DEC 16 1985
O.C.D.
HOBBS OFFICE