

UNIT STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

CONTACT RECEIVING
OFFICE FOR NUMBER
OF COPIES REQUIRED
(Other instructions re-
verse side)

BLM Roswell District
Modified Form No.
NM60-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		3a. Area Code & Phone No. 915/699-1410		5. LEASE DESIGNATION AND SERIAL NO. NM-13126	
2. NAME OF OPERATOR Stevens & Tull, Inc.				6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 11005, Midland, Texas 79702				7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 1650' FSL & 2310' FEL, Sec. 31, T-22-S, R-36-E				8. FARM OR LEASE NAME Meyer Federal	
14. PERMIT NO. unknown		15. ELEVATIONS (Show whether DF, RT, OR, etc.) 3512.8' GL		9. WELL NO. 1	
				10. FIELD AND POOL, OR WILDCAT Jalmat Yates SR	
				11. SEC., T., S., M., OR BLK. AND SURVEY OR AREA Sec. 31, T-22-S, R-36-E	
				12. COUNTY OR PARISH Lea	
				13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREAT

MULTIPLE COMPLETION

FRACTURE TREATMENT

ALTERING CASING

SHOOT OR ACIDIZE

ABANDON*

SHOOTING OR ACIDIZING

ABANDONMENT*

REPAIR WELL

CHANGE PLANS

(Other) Spud & run surface casing

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

- 1) Move in rig up. Spud well 2:30p.m. 1-23-90 local time.
- 2) Drill to 1421'. Good anhydrite shoe found at 1400' instead of proposed 1650'.
- 3) Ran 8 5/8 casing to 1421'. Use guide shoe, float collar, 14 centralizers.
- 4) Cement with 575 sacks "C" with 4% gel, 2% Calcium Chloride, 1/4# cellophane and 300 sacks "C" with 2% Calcium Chloride, 1/4# cellophane.
- 5) P.D. and float hold. Circulate 175 sacks cement.
- 6) BLM representative witnessed casing and cementing operations.
- 7) Change well number from No. 190 to No. 1. & add Federal to lease name

18. I hereby certify that the foregoing is true and correct

SIGNED Rodney L. Seale *Rodney L. Seale* TITLE Engineer

DATE 1/25/90

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

FEB 2 1990

*See Instructions on Reverse Side

SJS
CARLSBAD, NEW MEXICO