

(November 1983)
(Formerly 9-331)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPlicate
(Other instructions on
reverse side)

EXPIRATION DATE: 1001 OF 1
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM - 68821

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Federal 30

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Wildcat

11. SEC., T., R., M., OR B.M. AND
SURVEY OR AREA

Sec 30, T23S, R34E

12. COUNTY OR PARISH

Lea

13. STATE

New Mexico

SUNDRY NOTICES AND REPORTS ON WELLS RECEIVED

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☐ GAS WELL ☐ OTHER ☐

Weekly Drilling Report Aug 8 10 52 AM '90

2. NAME OF OPERATOR

Rosewood Resources, Inc.

3. ADDRESS OF OPERATOR

Suite 300, 200 Crescent Court, Dallas, Texas 75201

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

2080' FNL, 1980' FEL

14. PERMIT NO.

-

15. ELEVATIONS (Show whether OF, RT, GR, etc.)

GL - 3605.8

KB - 3617.3

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

Weekly Activity ☒

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-
nent to this work.)

1. Run 33 jts 8 5/8", 32#, S80, ST&C and 96 jts 8 5/8", 32#, K55, ST&C casing. Set at 5145'.
2. Cement with 1350 sx Premium Howco Lite + 18% salt + 1/4 #/sx flocele, tail in with 200 sx Premium Plus. Circulate 150 sx to surface.
3. WOC 8 hrs.
4. Cut off casing and weld on 11" - 3000# casinghead and NU BOPE. Test BOP's and choke manifold to 2000#.
5. Drilling 7 7/8" hole @ 7060'. 8-6-90.
6. Drill stem test the Ramsey sand @ 5185' - 5205' (20'). Zone was water bearing and non-productive.

8. I hereby certify that the foregoing is true and correct

SIGNED

TITLE

Drilling Manager

DATE

8-6-90

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.