

Submit to Appropriate
District Office
State Lease - 6 copies
Fee Lease - 5 copies
DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

State of New Mexico
Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

Form C-105
Revised 1-1-89

WELL API NO. 30-025-31096
5. Indicate Type of Lease STATE ☐ FEE ☒
6. State Oil & Gas Lease No. N/A
7. Lease Name or Unit Agreement Name Max Gutman
8. Well No. 10
9. Pool Name or Wildcat Brunson Drinkard-Abo, South

WELL COMPLETION OR RECOMPLETION REPORT AND LOG															
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____					1. Well Name or Unit Agreement Name Max Gutman										
b. Type of Completion: NEW WELL ☒ WORK OVER ☐ DEEPEN ☐ PLUG BACK ☐ DEEP RESVR ☐ OTHER _____															
2. Name of Operator Hanson Operating Company, Inc.					8. Well No. 10										
3. Address of Operator P. O. Box 1515, Roswell, New Mexico 88202-1515					9. Pool Name or Wildcat Brunson Drinkard-Abo, South										
4. Well Location Unit Letter <u>F</u> : <u>2310</u> Feet From The <u>North</u> Line and <u>1650</u> Feet From The <u>West</u> Line Section <u>19</u> Township <u>22S</u> Range <u>38E</u> NMPM Lea County															
10. Date Spudded 12/31/90		11. Date T.D. Reached 01/25/91		12. Date Compl. (Ready to Prod.) 02/28/91		13. Elevations (DF & RKB, RT, GR, etc.) 3339.5' GR		14. Elev. Casinghead							
15. Total Depth 7600'		16. Plug Back T.D. 7366'		17. If Multiple Compl. How Many Zones?		18. Intervals Drilled By Rotary Tools 0 - 7600'		Cable Tools							
19. Producing Interval(s), of this completion - Top, Bottom, Name 7039-7336' Drinkard								20. Was Directional Survey Made No							
21. Type Electric and Other Logs Run Dual Laterolog CBL, Compensated Z-Densilog Comp Neutron GR								22. Was Well Cored No							
23. CASING RECORD (Report all strings set in well)															
CASING SIZE		WEIGHT LB./FT.		DEPTH SET		HOLE SIZE		CEMENTING RECORD		AMOUNT PULLED					
13-3/8"		54.5#		350'		17-1/2"		350 sx Premium							
8-5/8"		32#		2550'		12-1/4"		975 sx Lite, 275 sx Premium							
5-1/2"		17#		7600'		7-7/8"		1st stage-630 sx "H"							
								2nd stage-400 sx Lite							
								& 100 sx Premium							
24. LINER RECORD										25. TUBING RECORD					
SIZE		TOP		BOTTOM		SACKS CEMENT		SCREEN		SIZE	DEPTH SET	PACKER SET			
N/A										2-7/8"	6981'	6981'			
26. Perforation record (interval, size, and number) 7039-7336' .44 28 holes										27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.					
										DEPTH INTERVAL		AMOUNT AND KIND MATERIAL USED			
										7039-7336'		3500 gal 15% NeFe acid			
												20000 gal 20% gelled acid			
28. PRODUCTION															
Date First Production 02/28/91		Production Method (Flowing, gas lift, pumping - Size and type pump) Flowing						Well Status (Prod. or Shut-in) Prod.							
Date of Test 03/07/91		Hours Tested 24		Choke Size 24/64		Prod'n For Test Period		Oil - Bbl. 135		Gas - MCF 375		Water - Bbl. 10		Gas - Oil Ratio 2778/1	
Flow Tubing Press. 50-250 psi		Casing Pressure 0		Calculated 24-Hour Rate		Oil - Bbl. 135		Gas - MCF 375		Water - Bbl. 10		Oil Gravity - API - (Corr.) 37.9			
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold.										Test Witnessed By David Sweeney					
30. List Attachments Form C-104, Deviation Survey, Logs															
31. I hereby certify that the information shown on both sides of this form is true and complete to the best of my knowledge and belief															
Signature <u>Brenda R. Godfrey</u>				Printed Name <u>Brenda R. Godfrey</u>				Production Analyst				Date <u>03/14/91</u>			

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, Items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy _____	T. Canyon _____	T. Ojo Alamo _____	T. Penn. "B" _____
T. Salt _____	T. Strawn _____	T. Kirtland-Fruitland _____	T. Penn. "C" _____
B. Salt _____	T. Atoka _____	T. Pictured Cliffs _____	T. Penn. "D" _____
T. Yates 2561	T. Miss _____	T. Cliff House _____	T. Leadville _____
T. 7 Rivers 2701	T. Devonian _____	T. Menefee _____	T. Madison _____
T. Queen 3380	T. Silurian _____	T. Point Lookout _____	T. Elbert _____
T. Grayburg _____	T. Montoya _____	T. Mancos _____	T. McCracken _____
T. San Andres 3930	T. Simpson _____	T. Gallup _____	T. Ignacio Otzte _____
T. Glorieta 5126	T. McKee _____	Base Greenhorn _____	T. Granite _____
T. Paddock 5152	T. Ellenburger _____	T. Dakota _____	T. _____
T. Blinberry 5520	T. Gr. Wash 7392	T. Morrison _____	T. _____
T. Tubb 6079	T. Delaware Sand _____	T. Todilto _____	T. _____
T. Drinkard 6297	T. Bone Springs _____	T. Entrada _____	T. _____
T. Abo _____	T. _____	T. Wingate _____	T. _____
T. Wolfcamp _____	T. _____	T. Chinle _____	T. _____
T. Penn _____	T. _____	T. Permian _____	T. _____
T. Cisco (Bough C) _____	T. _____	T. Penn "A" _____	T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from 5152 to 7392 No. 3, from _____ to _____
 No. 2, from _____ to _____ No. 4, from _____ to _____

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from _____ to _____ feet
 No. 2, from _____ to _____ feet
 No. 3, from _____ to _____ feet

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness in Feet	Lithology	From	To	Thickness in Feet	Lithology
Surf	2561'	2561'	Salt, sand & shale				
2561'	4893'	2332'	Dolomite				
4893'	5105'	212'	Limestone				
5105'	6550'	1445'	Dolomite				
6550'	7392'	842'	Limestone & dolomite				
7392'	TD	172'	Granite Wash				

MAR 1