

Form 3160-2
(July 1989)
(Formerly 9-111)

TIGHT HOLES
CONFIDENTIAL

N. M. OIL CONS. COMMISSION
BOY 1980
DEPARTMENT OF THE INTERIOR
HOBBS, NEW MEXICO 88240

CONTACT RECEIVING

BLM Roswell District
Modified Form No.
NM60-3160-4

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> Plugged and Abandoned		5. LEASE DESIGNATION AND SERIAL NO. NM-62224	
2. NAME OF OPERATOR Strata Production Company		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 1030, Roswell, New Mexico 88202-1030		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330' FSL & 2310' FEL		8. FARM OR LEASE NAME Aracanga Federal	
14. PERMIT NO. 30-025-31650		9. WELL NO. #1	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3677' GR		10. FIELD AND POOL, OR WILDCAT Wildcat Delaware	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Section 4-23S-32E	
		12. COUNTY OR PARISH Lea	
		13. STATE NM	

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANE ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

03/14/93: Drilled to 9000' TD. Ran logs and evaluated. Plugged and Abandoned as per BLM regulations and verbal approval. Witnessed by BLM representative. Cement plugs set as follows:

First Plug	8964' to 8664'	300'	95 sack Class "H" plug
			Tag top of plug at 8692'
Second Plug	6738' to 6638'	100'	50 sack Class "H" Neat plug
Third Plug	4753' to 4653'	100'	50 sack Class "H" Neat plug
Fourth Plug	4565' to 4465'	100'	50 sack Class "H" Neat plug
			in and out of intermediate casing
Fifth Plug	410' to 310'	100'	30 sack Class "H" Neat plug
			in and out of surface casing
Sixth plug	20' to surface 20'		15 sack Class "H" plug

Plug down at 12:00 noon 3/14/93.
Released rig at 4:00 PM on 3/14/93.
Dry Hole Marker installed

18. I hereby certify that the foregoing is true and correct

SIGNED Carol J. Garcia

TITLE Production Supervisor

DATE 4/7/93

(This space for Federal or State office use)

APPROVED BY (ORIG. SGD.) JOE G. LARA
CONDITIONS OF APPROVAL, IF ANY:

TITLE PETROLEUM ENGINEER

DATE 4/26/93

*See Instructions on Reverse Side

RECEIVED

JUL 09 1993

OCD HOD
OFFICE