Submit 3 Copies to Appropriate District Office

## State of New Mexico Energy, Minerals and Natural Resources Department

Form C-103

Revised 1-1-89

DISTRICT! P.O. Box 1980, Hobbs, NM 88240  OIL CONSERVATION DIVISION P.O. Box 2088  WELL API NO. 20, 025, 22180	
DISTRICT II P.O. Drawer DD, Artesia, NM 88210 Santa Fe, New Mexico 8	37504-2088 S Indiana Type of Lease
DISTRICT III 1000 Rio Brazos Rd., Aztec, NM 87410	STATE FEE X  6. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELL (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OF DIFFERENT RESERVOIR. USE "APPLICATION FOR PER (FORM C-101) FOR SUCH PROPOSALS.)	OR PLUG BACK TO A 7 Lease Name or Thirt Agreement Name
1. Type of Well: OR. GAS WELL X OTHER	
2. Name of Operator TEXACO EXPLORATION AND PRODUCTION INC.	8. Well No.
3. Address of Operator P. O. Box 3109 Midland, Texas 79702	9. Pool name or Wildow ( ) CS+ WILDOAT - BLINEBRY
4. Well Location  Unit Letter   1980   Feet From The   SOUTH   Line and   990   Feet From The   EAST   Line	
Section 33 Township 22-SOUTH Range 37-EAST NMPM LEA County  10. Elevation (Show whether DF, RKB, RT, GR, etc.)  GR-3335', KB-3349'	
11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data  NOTICE OF INTENTION TO:  SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK PLUG AND ABANDON	
TEMPORARILY ABANDON CHANGE PLANS	REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. PLUG AND ABANDONMENT
PULL OR ALTER CASING CASING TEST AND CEMENT JOB	
OTHER:	OTHER: PRODUCTION CASING
12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.	
1. DRILLED 7 7/8 HOLE TO 5800'. TD @ 11:15 PM 11-11-93. 2. HLS RAN GR-DLL-MSFL-CSL-CAL, GR-SDL-CNL FROM 5800' TO 3750'. PULLED GR-CNL TO SURFACE. 3. RAN 26 JOINTS OF 5 1/2, 15.5# LS-65, 17 JOINTS OF 15.5# J-55 AND 90 JOINTS OF 15.5# WC-50. LTC CASING SET @ 5800'. 4. DOWELL CEMENTED WITH 700 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 2% D46, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S). F/B 660 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 2% D46, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). PLUG DOWN @ 10:15 AM 11-12-93. CIRCULATED 64 SACKS. 5. ND. RELEASE RIG @ 6:00 PM 11-12-93. 6. PREP TO COMPLETE.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.  SIGNATURE C. P. BASHAM  THE DRILLING OPERATIONS MANAGER  DATE 11-15-93  TRESPHENNE NO. 915-6884620	
(This space for State Use) ORIGINAL SIGNED BY JERRY SEXTON	
DISTRICT I SUPERVISOR	NOV 22 1993
APPROVED BY TITLE	DAIB