For (Jui

Approved by Conditions of approval, if any:

TINE) STATES

. 5157	FORM APPROVED Budget Bureau No. 1004-0135
	FORM APPROVED
	Budget Bureau No. 1004-0135
14	Expires: March 31, 1993

Date _

SURDAY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drift for to deepen or reentry to a different reservoir. SUBMIT IN TRIPLICATE 1. Type of Well	June 1990) DEPARTMEN	T OF THE INTERIOR	Budget Bureau No. 1004-0135 Expires: March 31, 1993
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Substitution Substit			
SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. SUBMIT IN TRIPLICATE			NM-77077
SUBMIT IN TRIPLICATE Type of Well Gas Well Other Submit Other Other Submit Other Other		1	
SUBMIT IN TRIPLICATE 7. If Unit or CA. Agreement Designation 1. Type of Well 1. Type of Well 1. Type of Well 1. Well 1. Other 1. Subscription 1. Subscriptio	Do not use this form for proposals to dr Use "APPLICATION FO	ill or to deepen or reentry to a different reservents of the reservent of the reservents of the reservent of the reservents of the reservent of the reservent of the reservent of the reservents of the reservent of the rese	voir.
1. Type of Well Still Great State of State		7. If Unit or CA, Agreement Designation	
S. Weil Queil Other S. Weil Names and No. Jackal ANJ Federal #2 YATES PETROLEUM CORPORATION (505) 748-1471) 9. AH Weil No. 30-025-32233 10. Federal #2 Federal			
2. Name of Operator YATES PETROLEUM CORPORATION (505) 748-1471) 3. API Well No. 3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210 10. Eviden of World (Frouge, See, T. R. M., or Survey Description) 2310' FNL & 330' FWL of Section 4-T23S-R33E 11. County or Parish, State Lea Co., NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 13. Abandonment 14. Recompletion 15. Subsequent Report 16. Plinal Abandonment Notice 17. Altering Casting 18. Out-RESUME drilling; 18. Out-RESUME drilling; 19. Subsequent Report 19. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well directionally and square and zones pertinent to this work.) TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casting set at 1348'. Float schoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% Cacl2 and 1/2# cellosseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2.15 AM 9-4-93. Bumped plug to 950 psi; OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED FC OARLSBAD, NEW MEXICO Date Sept. 22, 194 Signed Wath Mark That Production Clerk Date Sept. 22, 194 Date Sept. 22, 194 CARLSBAD, NEW MEXICO Date Sept. 22, 194 Date Sept. 24 Date Sept. 24 Date Sept. 25			
3. Address and Telephone No. 105 South 4th St., Artesia, NM 88210 105 South 4th St., Artesia, NM 88210 106 Elevia and Tool, or Explorationy Area Wildcat 11. County or Parish, State Lea Co., NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF SUBMISSION Notice of Intent Subsequent Report Plant Abandonment Notice Abandonment Notice Abandonment Notice of Submission Non-Resture of Plant Abandonment Notice Altering Cating Other Resumed drilling a 12-1/4" hole with rotary tools at 3:00 AM 9-2-93. TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED FC CARLSBAD, NEW MEXICO Date Sept. 22, 194 Date Sept. 24			
10. South 4th St., Artesia, NM 88210 1. Location of Well (Flouge, Sec., T. R., M., or Survey Description) 2310' FNL & 330' FWL of Section 4-T23S-R33E 1. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 1. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 1. Check appropriate BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION 1. Check appropriate BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF ACTION 1. Notice of Intent 1. Abandonment 1. Abandonment 1. Change of Plans 1. Non-Rostine Frenching 1. Water Shut-Off 1. Casing Repair 1. Casing Repair 1. Casing Repair 1. Mere Resumed drilling; 1. Dispose Water 1. Ober Resumed and true vertical depths for all markers and concept epithent to this work.)* Resumed drilling a 12-1/4" hole with rotary tools at 3:00 AM 9-2-93. TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% Cacl2 and 1/2# celloseal (yield 1.99, weight 14.8). PD 12:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. 14. I hereby cript that the foregoing a prue and correct Suppose August 14.4. 15. Production Clerk 16. Description of Paths and correct Suppose August 14.8 and correct Suppose August 15.8 and correct Suppose August 15.		(505) 748-14/1)	9. API Well No.
4. Location of Well (Footage, See, T. R. M., or Survey Description) 2310' FNL & 330' FWL of Section 4-T23S-R33E 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent		30-025-32233	
2310' FNL 6 330' FWL of Section 4-T23S-R33E II. County or Parish, State Lea Co., NM IZ. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent Abandonment Recompletion Recompleti			
Lea Co., NM 12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA TYPE OF SUBMISSION TYPE OF ACTION Notice of Intent			
TYPE OF SUBMISSION TYPE OF SUBMISSION TYPE OF SUBMISSION Abandonment Abandonment Recompletion Plouging Back Casing Repair Altering Casing Oner-Resume drilling; Growersion to Injection Supressed and true vertical depths for all markers and zones pertinent to this work.)* To 13 A81'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 38 CacIl2 and 1/2# cellosseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped Plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. Title Production Clerk Date Sept. 22, 199	2310 FML & 330 FML OI BECC	10h 4-1255-R55E	
TYPE OF SUBMISSION Notice of Intent	·		
Notice of Intent	12. CHECK APPROPRIATE BOX	s) TO INDICATE NATURE OF NOTICE, R	EPORT, OR OTHER DATA
Recompletion New Construction New Construction	TYPE OF SUBMISSION	TYPE OF AC	TION
Subsequent Report	Notice of Intent	Abandonment	Change of Plans
Casing Repair Water Shut-Off Conversion to Injection Cheek Surface Csg & Cement Other Resorted and true vertical depths for all markers and zones pertinent to this work.)* To 1348' Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% Cacl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Carls Repair Water Shut-Off Conversion to Injection Dispose Water Note Repoir results of multiple completion on We complete when the West Report we were completed and we completed the West Report when the Mean we completed work. If we list discretionally drive we completed the West Report when the West Report we were completed to Work. If we list discretionally drive we can be a supported to the West Report when the West Report we were completed to Work. If we we support we were completed to Work. If we we support we were considered to we can be a supported work. If we we support we were considered to we we we will we were considered to we we we we we were considered to work.	_	Recompletion	
Final Abandonment Notice Altering Casing One Resume drilling; Dispose Water Notice Reportments of multiple completion on Water Resume drilling; Dispose Water Notice Reportments of multiple completion on Water Resumed drilling and proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drill give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Resumed drilling a 12-1/4" hole with rotary tools at 3:00 AM 9-2-93. TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIEDF(CARLSBAD, NEW MEXICO) Title Production Clerk Date Sept. 22, 199	Subsequent Report	Plugging Back	
Souther Resume drilling; Surface csg & Cement Choice Reportation on We completion on Proposed or Completed Operations (Clearly state all pertinent details, and give perinent dates, including estimated date of starting any proposed work. If well is directionally drill give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Resumed drilling a 12-1/4" hole with rotary tools at 3:00 AM 9-2-93. TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIEDF(COMPART CO			•
Surface CSG & Cement (Note: Report results of multiple completion of Romeletion Recompletion of Romeletion Recompletion for Romeletion Recompletion for Romeletion Recompletion for Romeletion Recompletion Recomplet	Final Abandonment Notice	Altering Casing Var. Posume drilling	
13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drill give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* Resumed drilling a 12-1/4" hole with rotary tools at 3:00 AM 9-2-93. TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED F(CARLSBAD, NEW MEXICO Title_Production Clerk Date Sept. 22, 199			+ (Note: Report results of multiple completion on Well
Resumed drilling a 12-1/4" hole with rotary tools at 3:00 AM 9-2-93. TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED FC CARLSBAD, NEW MEXICO Title_Production Clerk Date Sept. 22, 195			Completion of Recompletion Report and Log forms
TD 1348'. Ran 30 joints of 9-5/8" 36# J-55 (1350') of casing set at 1348'. Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED FC CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 19:	Describe Proposed or Completed Operations (Clearly state a give subsurface locations and measured and true vertical states are subsurface locations.)	uli pertinent details, and give pertinent dates, including estimated date of call depths for all markers and zones pertinent to this work.)*	starting any proposed work. It went is encountering the en-
Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED FC CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 199	Resumed drilling a 12-1/4	4" hole with rotary tools at	3:00 AM 9-2-93.
Float shoe set at 1348'. Float collar set at 1304'. Cemented with 400 sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED FC CARLSBAD, NEW MEXICO CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 199	TD 1348'. Ran 30 joints	of 9-5/8" 36# J-55 (1350') o	f casing set at 1348'.
sacks Pacesetter Lite "C", 3% CaCl2 and 1/2# celloseal (yield 1.99, weight 12.4). Tailed in with 250 sacks "C" Neat (yield 1.32, weight 14.8). PD 2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIEDF(CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 199	Float shoe set at 1348'.	Float collar set at 1304'.	Cemented with 400
2:15 AM 9-4-93. Bumped plug to 950 psi, OK. Circulated 141 sacks. WOC. Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPTED FC CARLSBAD, NEW MEXICO 14. I hereby corristy that the foregoing is true and correct Signed Waty Thur Title Production Clerk Date Sept. 22, 199	sacks Pacesetter Lite "C	", 3% CaCl2 and $1/2\#$ cellosea	1 (yield 1.99, weight
Drilled out at 3:15 AM 9-5-93. WOC 25 hours. Nippled up and tested to 25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIED F(CARLSBAD, NEW MEXICO CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 199	12.4). Tailed in with 2	50 sacks "C" Neat (yield 1.32	, weight 14.8). PD
25000 psi for 30 minutes. Reduced hole to 8-3/4". Resumed drilling. Notified BLM - no witness. CCEPIEDF(CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 199	2:15 AM 9-4-93. Bumped]	plug to 950 psi, OK. Circula	ted 141 sacks. WUC.
Notified BLM - no witness. CCEPIEDFC CARLSBAD, NEW MEXICO Id. 1 hereby coffir that the foregoing is true and correct Signed Luxty Llux Title Production Clerk Date Sept. 22, 199	Drilled out at 3:15 AM 9	-5-93. WOC 25 nours. Nippie	ed up and tested to
CCEPTED F(CARLSBAD, NEW MEXICO Title Production Clerk Date Sept. 22, 199	Notified RIM - no witness	Reduced Noie to 0 3/4 : 1	. DO 5
CCEPTED F(CARLSBAD, NEW MEXICO Signed Lusty Title Production Clerk Date Sept. 22, 199	Notified bin no without		
14. I hereby certify that the foregoing is true and correct Signed Lusty Llew Title Production Clerk Date Sept. 22, 199		CCEPTED FC	
14. I hereby certify that the foregoing is true and correct Signed Lusty Llew Title Production Clerk Date Sept. 22, 199			σ
14. I hereby certify that the foregoing is true and correct Signed Lusty Llew Title Production Clerk Date Sept. 22, 199		₹ 1.4 .0 7 # 9 € 7	TO THE PARTY OF TH
14. I hereby certify that the foregoing is true and correct Signed Lusty Llew Title Production Clerk Date Sept. 22, 199			6 m
14. I hereby certify that the foregoing is true and correct Signed Lusty Llea Title Production Clerk Date Sept. 22, 199	•		
Signed Kusty Title Production Clerk Date Sept. 22, 199		CARLSBAD, NEW	MEXICO Section 1
	14. I hereby certify that the foregoing is true and correct	rg v about de transportation of the	0);11
	Signed Kusty Fleen	TideProduction Clerk	Date Sept. 22, 1993
(Tuis abace for Lenetafor grave office gae)	(This space for Federal or State office use)		• 14

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

Title _____