

Form 3160-5
(June 1990)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Strata Production Company

3. Address and Telephone No.

P.O. Box 1030, Roswell, NM 88202-1030

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL & 660' FWL
Section 27-23S-34E

5. Lease Designation and Serial No.

LC-071949

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Papagayo Federal #1

9. API Well No.

30-025-32543

10. Field and Pool, or Exploratory Area

Antelope Ridge Bone Spring
11. County or Parish, State West

Lea County, NM

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Production Casing and Cement
☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water
(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

7/06/94: Drilled to 8900' TD. Ran 96 joints (3842.63') 5 1/2" L80 LTNC 17# casing and 130 joints (5067.53') 5 1/2" J55 LTNC 17# casing. Set DV tool at 6414'. Cemented First Stage at 8900' with 680 sacks 50/50 Poz H with 5# D44, 3/10% D60, 2.5# B28, 1/4# D29 and 2/10% D46 per sack. Circulated 147 sacks to pit. Plug down at 2:30 AM on 7/6/94. Cemented Second Stage with 295 sacks 35/65 Poz C with 6/10% D20, 8# D44 and 1/4# D29 per sack. Tail in with 100 sacks Class "C" Neat. Plug down at 7:30 AM on 7/6/94. Waiting on cement. Rig released at 11:30 AM on 7/6/94.

J. Lara

14. I hereby certify that the foregoing is true and correct

Signed Carol J. Garcia

Title Production Records Manager

Date 8/10/94

(This space for Federal or State office use)

Approved by _____
Conditions of approval, if any:

Title _____

Date _____