Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR

FORM APPROVED Budget Bureau No. 1004-0135

We

Expires: March 31, 1993

-			, , , , , , ,	
5.	Lease	Designation and	Serial No.	
		1949		

SUNDRY NOTICES Do not use this form for proposals to dr	AND REPORTS ON WELLS ill or to deepen or reentry to a different reservoire R PERMIT—" for such proposals	5. Lease Designation and Serial No. LC-071949 6. If Indian, Allottee or Tribe Name
SUBMIT	7. If Unit or CA, Agreement Designation	
Type of Well Oil Gas Well Well Other 2. Name of Operator	8. Well Name and No. Papagayo Federal #1	
Strata Production Company 3. Address and Telephone No. P.O. Box 1030, Roswell, NM 88	9. API Well No. 30-025-32543 10. Field and Pool, or Exploratory Area	
4 Location of Well (Footage, Sec., T., R., M., or Survey De 660' FSL & 660' FWL Section 27-23S-34E	Antelope Ridge Bone Spring 11. County or Parish, State Lea County, NM	
12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPOR	T, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment Recompletion	Change of Plans New Construction
Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
☐ Final Abandonment Notice	Altering Casing X Other <u>Spud and Surface and</u> intermediate casing and ceme	Conversion to Injection Dispose Water Note: Report results of multiple completion on Well
13 Describe Proposed or Completed Operations (Clearly state all give subsurface locations and measured and true vertical	pertinent details, and give pertinent dates, including estimated date of starting a depths for all markers and zones pertinent to this work.)*	any proposed work. If well is directionally drilled.
6/17/94: MIRU. Spud 17	1/2" hole at 6:00 PM on 6/17/94	. Drilled to 552'.

Ran 12 joints (555.82') 13 3/8" 48# H40 casing. Cemented at 552' <u>6/18/94</u>: with 700 sacks PP with .2% D-46, 1/4 # D-29, and 2% CaCL per sack.

Plug Down at 9:00 AM on 6/18/94. WOC.

- 6/19/94: NU BOP. Pressure test to 1000#. Held OK.
- 6/26/94 Drilled to 4871'. Ran 114 joints (3028'-32#) and (1850'-24#) 8 5/8" 24# and 32# HCK55 LT&C and J55 ST&C casing. Cemented at 4871' with 1130 sacks 50/50 C & B-44, 15# D-44, 1/4# D-29, and 2% D-46 per sack. Tail-in with 200 sacks Class "C" with 1% CaCL per sack.

Circulate 136 sacks to pit. Plug down at 1:30 AM on 6/26/94. WOC.

6/27/94: NU BOP. Pressure test to 1100#. Held OK.

Ad	_		
	,	8	190 <u>/</u> 1

		. V 100 mp
14. I hereby pertify that the foreguing is true and correct Signed Arol J. Parcia	Production Records Manager	7/1/94
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Title	Date

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.