P.O. BOX 1980	
SEIVED	HOBBS, NEW MEXICO 88240
Form 3160-5 RECEIVED (June 1990) UNITED STATES (June 1990) UNITED STATES UNITED STATES UNITED STATES UNITED STATES	FORM APPROVED Budget Bureau No. 1004-0135 Expires: March 31, 1993 5. Lease Designation and Serial No.
NOV 10 NOV 10 Do not use this form for proposals to drill or to deepen or reentry to LSC Use "APPLICATION FOR PERMIT—" for such prop	LS <u>NM - 0587</u> 6. If Indian, Allottee or Tribe Name o a different reservoir.
SUBMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1       T; pc of Well         Oil       X Well         Well       X Well         2       Name of Operator         AMERADA HESS CORPORATION         3       Address and Telephone No.         P.O. BOX 2040       HOUSTON, TEXAS 77252         4       Location of Well (Footage, Sec., T., R., M., or Survey Description)         1100'       FSL & 1500'         FWL SEC 5       T \$\alpha\$ \$\alp	8. Well Name and No. NORTH_BELL_LAKE #2 9. API Well No. 30-025-32672 10. Field and Pool, or Exploratory Area N. BELL_LAKE 11. County or Parish, State LEA, NM.
12 CHECK APPROPRIATE BOX(s) TO INDICATE NATURE	
Notice of Intent     Abandonment     Recompletion	
X Subsequent Report	Non-Routine Fracturing
Final Abandonment Notice	Water Shut-Off Conversion to Injection UD AND CEMENTING UNit: Report results of multiple completion of Water (Note: Report results of multiple completion of Water)

Sec. Systems

M.I. & R.U. ROWAN DRILLING RIG #31 AND SPUDDED 26" HOLE @ 11:30 P.M. 09-29-94. DRILLED TO 909'. R.U. RAN AND CMTD 21 JTS. 20" 94# X-56, R-3, ST & C CSG. CMTD 868 SKS CLASS "C". CMT. TO SURFACE, TAILED W/200 SKS CLASS "C". CIRC. 161 SKS. CMT. TO SURFACE. BLM REP. PATRICIA A. HUTCHINGS WIT CMT. JOB. INSTALLED 20" 3000# CASINGHEAD 11:00 A.M. 10-08-94. TEST CSG. & HYDRIL TO 1500 PSI FOR 30 MIN. HELD 0.K. CIRC. DOWN TO 893' TAG CMT @ 893'. DRLG 17-1/2" HOLE FROM 917'-4,875'. R.U. & RAN 65 JTS. 13-3/8" 68# J-55 ST & C R-A "A" CSG, 1 JT. 13-3/8" J-55 BUTT. PIN X ST & C BOX, 36 JTS. 13-3/8" 72# N-80 BUTT. R-3 "A", 16 JTS. 13-3/8" 72# P-110 BUTT. R-3 "A" AND A 13-3/8" FLOAT SHOE. CMT. CSG W/4100 SXS. CLASS "C" 35/65 POZ MIX 67% D-20, 10% D-44, 2% D-13. TAILED W/500 SXS CLASS "H" W/1% D-13. DISPLACED PLUG W/716 BFW. BUMPED PLUG TO 2500 PSI. PLUG DOWN & HOLDING @ 4:30 A.M. MST. 10-23-94. CIRC. 300 SXS CMT. TO SURFACE 10-25-94 7:00 P.M. TEST CSG. TO 1500 PSI. HELD FOR 30 MIN.

TEST CSG. TO 1500 PSI. HELD FOR 30 MIN.	ACCEPTED FOR F		
•		NOV 1 5 1994	
14. I hereby certify that the foregoint is true and correct		CARLSBAD, NEW MEALCE	
signed mile funper	Title SUPERVISOR	DRILLING SERVICES Date <u>11-08-94</u>	
(This space for Federal or State office use) Approved by Conditions of approval, if any:	Tide	Date	

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.