Form 3160-5 (June 1990)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

P.O. BCX 1880 HOBBS BNEW MEXICOL 88240

Expires:	March	31,	1993
----------	-------	-----	------

SUNDRY NOTICES AND REPORTS ON WELLS Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		5. Lease Designation and Serial No. NM 18848	
The state of the s	FOR PERMIT" for such proposals	6. If Indian, Alottee or Tribe Name	
SUBM	MIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation	
1. Type of Well: OIL GAS WELL	OTHER	Well Name and Number SDE '31' FEDERAL	
Name of Operator TEXACO EXPLOR	ATION & PRODUCTION INC.	9	
	enver Colorado 80201-6510 (303)621-485	9. API Well No. 30-025-32868	
4. Location of Well (Footage, Sec., T., R., M., or Surve Unit Letter J: 1980 Feet From T	he SOUTH Line and 1980 Feet From The	10. Field and Pool, Exploratory Area TRISTE DRAW WEST, SAND DUNES SOUTH BONE	
EAST Line Section 31	Township 23-S Range 32-E	11. County or Parish, State LEA , NM	
12. Check Appropriate	Box(s) To Indicate Nature of Notice, Re	eport, or Other Data	
TYPE OF SUBMISSION		YPE OF ACTION	
 Notice of Intent Subsequent Report Final Abandonment Notice 	Abandonment Recompletion Plugging Back Casing Repair Altering Casing OTHER: COMPLETION	Change of Plans New Construction Non-Routine Fracturing Water Shut-Off Conversion to Injection Dispose Water (Note: Report results of multiple completion on Well	
13 Describe Proposed or Completed Occasions (Class		(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)	

- Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is
 directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*.
- RU SCHLUMBERGER. RAN GR-CBL FROM 9574'-4300'. 04-12-95. PERF'D THE BRUSHY CANYON W/ 2 JSPF FROM 8266'-8298', 8413'-8437'. 112 HOLES.
- 2. DOWELL ACIDIZED THE BRUSHY CANYON PERFS W/ 2000 GAL 15% NEFE. FRAC'D W/ 35,000 GAL 30# BORATE XLG CARRYING 134,000# 20/40 OTTOWA SAND AND 24,000# 16/30 RESIN COATED. FLOWED 330 BLW IN 6 HOURS ON 32/64" CHOKE. 04-14-95.
- 3. MIRU POOL WS. TIH W/ PKR ON 1 JT TBG AND SET. 04-16-95.
- 4. TIH W/ NOTCHED COLLAR TO 8700'. DID NOT TAG ANY SAND. TOH W/ TBG AND NOTCHED COLLAR. TIH W/ PRODUCTION EQUIP. BOTTOM MA @ 8482, SN @ 8451, TAC @ 8138. 04-19-95.
- TIH W/ 2.5" X 1.75" X 20' PUMP AND 127 RODS. 04-20-95.
- 6. PUT ON PUMP TEST. 04-22-95. PM 86 BO, 346 BW, 146 MCF IN 24 HOURS 04-26-95.

J fara 5 1995

14. I hereby certify that the foregoing is true and SIGNATURE	Dasham (SRH TITLE Drilling Operations Mgr.	DATE	4/28/95
TYPE OR PRINT NAME	C. P. Basham		
(This space for Federal or State office use)			
APPROVED BYCONDITIONS OF APPROVAL, IF	TITLETITLE	DATE	

RECEIVED

OFFICE