4.m. OIL CONS. COMMISSION P.O. BOX 1980 ACORS NEW MEXICO 88240 UNITED STATES Form 3160-5 DEPARTMENT OF THE INTERIOR (June 1990) Budget Bureau No. 1004-0135 BUREAU OF LAND MANAGEMENT Expires: March 31, 1993 5. Lease Designation and Serial No. SUNDRY NOTICES AND REPORTS ON WELLS NM-18848 ૂર્વ bo not use this form for proposals to drill or to deepen or reentry to a different reservoir. 6. If Indian, Alottee or Tribe Name Use "APPLICATION FOR FERMIT -- " for such proposals 7. If Unit or CA, Agreement Designation SUBMIT IN TRIPLICATE OIL WELL 8. Well Name and Number GAS 1. Type of Well: CJ OTHER SDE '19' FEDERAL 2. Name of Operator 3 **TEXACO EXPLORATION & PRODUCTION INC.** 3. Address and Telephone No. 9. API Well No. P.O. Box 46510, Denver Colorado 80201-6510 (303)621-485 4. Location of Well (Footage, Sec., T., R., M., or Survey Description) 10. Field and Pool, Exploratory Area TRISTE DRAW WEST & SAND DUNES SOUTH BONE Feet From The SOUTH Line and 2310 Feet From The 11. County or Parish, State Line Section 19 Township 23-S Range 32-E LEA , NM 12 Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data TYPE OF SUBMISSION TYPE OF ACTION Abandonment Change of Plans **New Construction** Recompletion Notice of Intent Plugging Back Non-Routine Fracturing Subsequent Report Water Shut-Off Casing Repair Conversion to Injection Altering Casing Final Abandonment Notice OTHER: Dispose Water (Note: Report results of multiple co 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work,)* CSG PROGRAM: 11-3/4" 42# WC-40 SET @ 550'. 8-5/8", 24# WC-50 SET @ 4500'. 5-1/2" 15.5# K-55 7500" 5-1/2" 17# K-55 1700' 5-1/2" 17# L-80 650 SET @ 9850' **CEMENTING PROGRAM:** SURFACE CASING -400 SACKS CLASS C W/ 2% CACL2 (14.8 PPG, 1.34 CF/SX, 6.3 GW/S). INTERMEDIATE: LEAD: 1200 SXS 35/65 POZ H W/ 6% GEL, 5% SALT, 1/4#/SX, FLOCELE @ 12.4 PPG, 2.14 CF/SX. TAIL: 150 SXS CLASS H NEAT @ 15.6 PPG, 1.18 CF/SX. PRODUCTION CASING - Tail: 750 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/SX). Lead: 350 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.4 PPG, 2.14 CF/SX). VERBAL APPROVAL WAS GIVEN BY SHANNON SHAW. 14. I hereby certify that the foregoing is true and correct SIGNATURE C.P. Bacham SRH TITLE Drilling Operations Mgr. TYPE OR PRINT NAME

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction

PETROLEUM ENGINEER

(This space for Federal or State (ORIG. SCD.) JOE G. LARA

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY: