

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

P.O. BOX 1980
HOBBS, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☐ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC

3. Address and Telephone No.
P.O. Box 46510, Denver Colorado 80201-6510 (303)621-485

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter N 660 Feet From The SOUTH Line and 1980 Feet From The

WEST Line Section 31 Township 23-S Range 32-E

5. Lease Designation and Serial No.
NM-18848

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and Number
SDE '31' FEDERAL

9. API Well No.
30-025-32915/6

10. Field and Pool, Exploratory Area
TRISTE DRAW WEST & SAND DUNES SOUTH BONE

11. County or Parish, State
LEA NM

Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

TYPE OF ACTION

- ☐ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ OTHER: SPUD, SURF, INT, PROD CSG

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion or well Completion or Recompletion Report and Log Form 1)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

- PETERSON RIG SPUD 14-3/4" INCH HOLE @ 5:30 PM 05-16-95. DRILLED TO 550'.
- RAN 13 JOINTS OF 536', 11-3/4, 42#, WC-40, STC CASING SET @ 550'.
- DOWELL CEMENTED WITH 400 SACKS CLASS C W/ 2% CACL2 (14.9 PPG, 1.34 CF/S). PLUG DOWN @ 5:30 PM 05-17-95. CIRCULATED 98 SACKS.
- NU BOP & TESTED TO 1200# TESTED CASING TO 1200# FOR 30 MINUTES FROM 7:30 AM TO 8:00 AM 05-18-95.
- WOC TIME 14 HOURS FROM 5:30 PM 05-17-95 TO 7:30 AM 05-18-95.
- DRILLING 11 INCH HOLE
- DRILLED 11 INCH HOLE TO 550'. TD @ 5:30 AM 05-17-95.
- RAN 48 JOINTS OF 8 5/8, 32# K-55 AND 61 JOINTS OF 24#, K-55, LTC CASING SET @ 4454'. RAN 3 CENTRALIZERS.
- DOWELL CEMENTED W/ 1200 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S) F/B 150 SACKS CLASS H (15.6 PPG, 1.13 CF/S). PLUG DOWN @ 5:30 PM 05-17-95. CIRCULATED 98 SACKS.
- NU BOP AND TESTED TO 1200# TESTED CASING TO 1200# FOR 30 MINUTES FROM 7:30 AM TO 8:00 AM 05-18-95.
- WOC TIME 14 HOURS FROM 5:30 PM 05-17-95 TO 7:30 AM 05-18-95.
- DRILLING 7 7/8 HOLE.
- DRILLED 7 7/8 HOLE TO 9850'. TD @ 1:00 PM 06-01-95.
- HLS RAN LOG RUN NO 1: GR-HRI FROM 4478'-9850'. LOG RUN NO 2: GR-SDL-DSN, FROM 4478' TO 9850'. PULL GR-DSN TO SURFACE.
- RAN 16 JOINTS OF 5 1/2, 17#, L-80, 39 JOINTS OF 5 1/2, 17#, K-55 AND 166 JOINTS OF 5 1/2, 15 5/8 K-55, LTC CASING SET @ 9850'.
- DOWELL CEMENTED WITH 255 SACKS 35/65 POZ CLASS H W/ 6% GEL, 5% SALT, 1/4# FLOCELE (12.8 PPG, 1.94 CF/S) F/B 161 SACKS 50/50 POZ CLASS H W/ 2% GEL, 5% SALT, 1/4# FLOCELE (14.2 PPG, 1.35 CF/S). PLUG DOWN @ 1:15 PM 06-03-95. CIRCULATED 0 SACKS. TOP OF CMT @ 3750' BY CBL.
- ND. RELEASE RIG @ 5:00 PM 06-03-95
- PREP TO COMPLETE

14. I hereby certify that the foregoing is true and correct.

SIGNATURE C. P. Basham (SR) TITLE Drilling Operations Mgr.

DATE 6/22/95

TYPE OR PRINT NAME C. P. Basham

(This space for Federal or State office use)

APPROVED BY TITLE

DATE J. Lara

CONDITIONS OF APPROVAL, IF ANY:

The 18 U.S.C. Section 1001 makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.