

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons. Division
P.O. Box 1980
Hobbs, NM 88241
FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

RECEIVED

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT --" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well: ☒ OIL WELL ☐ GAS WELL ☐ OTHER

2. Name of Operator
TEXACO EXPLORATION & PRODUCTION INC.

3. Address and Telephone No. P.O. Box 2100, Denver Colorado 80201 (303)621-4851

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

Unit Letter O : 660 Feet From The SOUTH Line and 1980 Feet From The

EAST Line Section 31 Township 23-S Range 32-E

8. Well Name and Number
SDE '31' FEDERAL

9. API Well No.
30-025-32917

10. Field and Pool, Exploratory Area
TRISTE DRAW WEST & SAND DUNES SOUTH BONE

11. County or Parish, State
LEA, NM

12. Check Appropriate Box(s) To Indicate Nature of Notice, Report, or Other Data

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ OTHER: COMPLETION

TYPE OF ACTION

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log Form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1. RU SCHLUMBERGER. RIH W/ CBL GR & CCL. LOGGED UP FROM 8468' TO 1650'. TOC @ 1900'. 02-13-97.
2. RU SCHLUMBERGER. RIH W/ 4" GASED GUNE. CORRELATED F/DEPTH. PERF'D: 8268'-8292' W/ 4 JSPF. 96 HOLES. 02-14-97.
3. DOWELL ACIDIZED W/2000 GALS 7-1/2% HCL NEFE ACID. FRAC'D W/ 32,000 GALS 36# BORATE CROSSLINKED GEL & 100,000# 16/30 RESIN COATED PRECURED AND CURABLE OTTAWA SAND. 02-18-97.
4. TIH W/ TBG. TAGGED SAND @ 7385'. 02-21-97. RAN 2-1/2" X 1.73" X 2-1" PUMP, K-BARS, RODS. SN @ 8200'. 02-22-97.
5. POH W/ RODS & PUMP, JTS, TBG, TAC, SN & MUD ANCHOR. 03-06-97.
6. RIH W/ BAKER WLS/TBG RET BRIDGE PLUG. CORRELATED F/ DEPTH. SET PLUG @ 8180'. DUMPED 10' SAND ON PLUG. PERF'D: 7223'-7245' W/ 4 JSPF. 88 HOLES. 03-07-97.
7. DOWELL ACIDIZED THE UPPER BRUSHY CANYON W/2,000 GALS 7-1/2% NEFE HCL. FRAC'D W/10,000 GALS 35# BORATE CROSSLINKED GEL & 20,000# 16/30 OTTAWA RCS. 03-08-97.
8. RAN 2 1/2" X 1.75" X 24' PUMP, RODS, K-BARS. WELL ON PUMP 1:00 PM 03-10-97.
9. PUMPED 60 BBLS 2% KCL DOWN CSG & 30 BBLS DOWN TBG TO KILL WELL. TOH W/ RODS & PUMP 03-25-97.
10. PUMPED 60 BBLS 2% KCL DOWN CSG & 30 BBLS DOWN TBG TO KILL WELL. N/D BOP. P/U 2-1/2" X 1.75" X 24' PUMP, RODS. 03-02-97.
11. RIH W/ TBG RET BRIDGE PLUG. CORRELATE F/DEPTH. SET PLUG @ 7110'. RIH W/ DUMP BAILER. DUMPED 10' SAND ON PLUG. PERF'D: 4708'-4728' W/ 4 JSPF. 80 HOLES. 05-05-97.
12. DOWELL ACIDIZED RAMSEY SAND W/2200 GALS 7-1/2% HCL NEFE. 05-06-97.
13. PU 2 1/2" X 1 3/4" X 22' PUMP, SUB. RAN IN HOLE W/ K-BARS, RODS, SUBS. 05-07-97. REL PKR. POOH. 05-20-97.
14. TIH W/ TBG TO 8340'. N/D BOP. P/U 2 1/2" X 1 3/4" X 22' PUMP. TIH W/ RODS. 05-28-97.
15. OPT: PUMPED 56 BO, 105 MCFD, 135 BW. 06-01-97.

14. I hereby certify that the foregoing is true and correct

SIGNATURE C.P. Basham / SRE TITLE Eng. Assistant.

DATE 6-5-97

TYPE OR PRINT NAME Sheilla D. Reed-High

(This space for Federal or State office use)

APPROVED

CONDITIONS OF APPROVAL, IF ANY: TITLE DATE

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.