

HOLE PROGNOSIS  
CODORNIZ FEDERAL #2  
PAGE 2

4. Casing Program:

<u>Hole Size</u>	<u>Interval</u>	<u>OD Csg</u>	<u>Weight, Grade, Jt. Cond, Type</u>
17 1/2"	0-600'	13 3/8"	48#, H-40, ST&C, New
12 1/4" & 11"	0-4750'	8 5/8"	24# & 32#, J-55, S-80, LT&C, New
7 7/8"	0-TD	5 1/2"	17# & 15.5#, K-55, LT&C, New

5. Cementing Program:

Surface Casing: 13 3/8" casing will be set at approximately 600' and cemented with approximately 700 sacks of Premium Plus cement with 2% CaCl and additives. The amount may be adjusted depending upon the fluid caliper results, however, cement in sufficient quantities to circulate will be utilized.

Intermediate Casing: 8 5/8" casing will be set at approximately 4750' and cemented with approximately 1900 sacks of 35/65 Poz "C" with additives, and 200 sacks Class "C" with 2% CaCl. The amount may be adjusted dependent upon fluid caliper results, however, cement in sufficient quantities to circulate will be utilized.

Production Casing: If appropriate, 5 1/2" casing will be set at Total Depth. Strata utilizes cement in sufficient quantities to circulate cement into the 8 5/8" intermediate casing in two (2) stages. The first stage to be cemented with approximately 600 sacks 50/50 Poz "H" with additives. The second stage to be cemented with approximately 200 sacks of 35/65 Poz "C" with additives, and 100 sacks of Class "C" Neat.