

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
N.M. OIL CONS. COMMISSION
P.O. BOX 1980
CORRAL NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993
Designation and Serial No.

NM-0559539

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Harvard Petroleum Corporation

3. Address and Telephone No.

P.O. Box 936, Roswell, New Mexico 88202-0936 (505) 623-1581

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

660' FSL, 2310' FEL, Sec. 19-T23S-R32E

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

James Federal "19" #1

9. API Well No.

30-025-33085

10. Field and Pool, or Exploratory Area

South Sand Dunes Bone Spring

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Run Surface Casing

☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

10/12/95 Spud well, notify BLM, Betty Cox.

10/13/95 Drill to 535'. Run 12 jts (541.17') 13 3/8" K55, 48# csg. and set at 535'. Cmt w/270 sx 65/35 Poz "C" w/6% Gel, 2% CaCl & 1/4 lb/sk Cello-Seal. Tail w/200 sx Class "C" w/2% CaCl. Bump plug @ 3:45 p.m. & circ. 50 sx to pit. WOC 12 hrs. Set slips, cut off & weld on "A" section and NU BOP. Test BOP & csg. to 1200 psi.

14. I hereby certify that the foregoing is true and correct

Signed

Title Vice President

Date 11-21-95

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: