

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

M. OIL CONS. CO.
P.O. BOX 1980
CORRAL BLANCO, NEW MEXICO 88240

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator
Harvard Petroleum Corporation

3. Address and Telephone No.

P.O. Box 936, Roswell, NM 88202-0936 (505) 623-1581

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 2310' FEL
Sec. 19-T23S-R32E

5. Lease Designation and Serial No.

NM-0559539

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

James Federal "19" #2

9. API Well No.

30-025-33100

10. Field and Pool, or Exploratory Area

S. Sand Dunes Bone Spring

11. County or Parish, State

Lea

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent
☒ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☒ Other Run Surface Csg.

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

3/18/96 Spud well @ 7 :15 p.m., notify BLM (Rick)

3/19/96 Drill 17 1/2" hole to 536'. Run 12 JTS (542.97') 13 3/8" K-55, 48# csg. & set @ 536'. Cmt. w/ 270 sks 35/65 Poz "C" w/ 6% gel, 2% CaCl & 1/4# sk Cello-Seal. Tail w/ 200 sks "C" w/ 2% CaCl. Bump plug @ 12:15 a.m. 3/20/96, circ. 78 sks to pit. Set slips, cut off & weld on "A" section, NU & test BOP to 1200 psi.

ACCEPTED
J. Lora
4/25/1996

LEA, NEW

14. I hereby certify that the foregoing is true and correct

Signed

Title Jeff Harvard, Vice President

Date 4/25/96

(This space for Federal or State office use)

Approved by

Title

Date

Conditions of approval, if any: