

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

U.S. DEPT. OF THE INTERIOR
P. O. BOX 1800
ROSWELL, NEW MEXICO 87003

ROSWELL DISTRICT COPY

FORM APPROVED
Budget Bureau No. 1004-0135
Expires: March 31, 1993

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.
Use "APPLICATION FOR PERMIT-" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well

☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator

Penwell Energy, Inc.

3. Address and Telephone No.

600 N. Marienfeld, Suite 1100, Midland, TX 79701, 915-683-2534

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FWL, Sec. 24, T23S, R32E

5. Lease Designation and Serial No.

NM-86154

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No.

Diamondtail "24" Fed #1

9. API Well No.

30-025-33344

10. Field and Pool, or Exploratory Area

Diamondtail Bone Springs

11. County or Parish, State

Lea County, New Mexico

12. CHECK APPROPRIATE BOX(S) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☒ Notice of Intent
☐ Subsequent Report
☐ Final Abandonment Notice

TYPE OF ACTION

- ☒ Abandonment
☐ Recompletion
☐ Plugging Back
☐ Casing Repair
☐ Altering Casing
☐ Other

- ☐ Change of Plans
☐ New Construction
☐ Non-Routine Fracturing
☐ Water Shut-Off
☐ Conversion to Injection
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

DIAMONDTAIL "24" FEDERAL #1

- Run tbg. to 10,150'.
- Load hole with 250 bbls. gelled brine.
- Spot 225 sx. cement 8,120' - 10,150', across perms 8,247' - 8,253', 8,994' - 9,030' & 10,029' - 10,082'.
- Spot 25 sx. cement 500' - 730'.
- Spot 5 sx. cement 3' - 10'. 50' minimum surface plug.
- Cut off wellhead. Cap with 1/4" steel plate.

* additional plug: 150' minimum, centered on 8 5/8" casing shoe.

RECEIVED
1998 JUL 31 A 11:49
BUREAU OF LAND MGMT.
ROSWELL, NEW MEXICO

14. I hereby certify that the foregoing is true and correct

Signed Russell L. Colett

Title Engineer

(This space for Federal or State office use)

Approved by
Conditions of approval, if any:

Title

APPROVED *as modified*
PETER W. CHESTER

AUG 24 1998

Date 07/29/98

BUREAU OF LAND MANAGEMENT
ROSWELL RESOURCE AREA

Date