

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.

Use "APPLICATION FOR PERMIT -" for such proposals

SUBMIT IN TRIPLICATE

1. Type of Well ☒ Oil Well ☐ Gas Well ☐ Other	5. Lease Designation and Serial No. NM 62225
2. Name of Operator Meridian Oil Inc.	6. Well Name, Allotment or Tribe Name
3. Address and Telephone No. P.O. Box 51810, Midland, TX 79710-1810 915-688-6943	7. If Unit or CA, Agreement Designation
4. Location of WCE (Footage, Sec., T., R., M., or Survey Description) 660' FSL & 1980' FML Sec. 34, T23S, R32E	8. Well Name and No. Diamond "34" # 3 Federal
	9. API Well No.
	10. Field and Pool, or exploratory Area West Triste Draw Delaware
	11. County or Period, State Lea NM

12. CHECK APPROPRIATE BOX(es) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION
☐ Notice of Intent	☐ Abandonment
☐ Subsequent Report	☐ Reconception
☐ Final Abandonment Notice	☐ Plugging Back
	☐ Casing Repair
	☒ Altering Casing
	☒ Other: And Cement Program
	☐ Change of Plans
	☐ New Construction
	☐ Non-Routine Plugging
	☐ Water Shut-Off
	☐ Conversion to Injection
	☐ Dispose Water

13. Direction Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent data, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and trend and true vertical depths for all sections and zones pertinent to this work.)*

Meridian Oil Inc. respectfully requests approval to change the casing and cement program for the proposed new drill well. See below

Surface: 12 1/4" hole, 9 5/8" 36# H-40 csg set @ 650'. Cmt w/lead-150 sxs 'C' + 4% gel + 2% CaCl2 + 1/4 pps flocele, tail w/200 sxs 'C' + 2% CaCl2 + 1/4 pps flocele. Circ. to surf.

Inter: 8 3/4" hole, 7" 23#/26# K-55/H-80 csg set @ 4650'. Cmt w/lead-470 sxs 'C' + 1 pps econolite + 1 pps flocele + 5 pps gilsonite, tail w/200 sxs 'C' + 2% CaCl2. Circ. to surf.

Production: 6 1/8" hole, 4 1/2" 11.6# N-80 csg set @ 10,200'. Cmt w/lead-110 sxs 'C' + 3% econolite + 1/4 pps flocele, tail w/320 sxs 'H' 50/50 Poz + 2% gel + 3 pps KCl + .6 Halad-9 + 1/4 pps flocele. TOC @ +/- 4400'.

BOP: 11" 3M BOP on the 9 5/8" csg and the 7" csg. Consist of one blind ram BOP, one pipe ram BOP and a rotating head. Will test to 1500 psi before drlg shoe.

14. I hereby certify that the foregoing is true and correct.

Signed: [Signature] Title: Regulatory Compliance Date: 3/28/96

(This space for Federal or State official use)

Approved by: S. Shaw Title: Petrol. Engr. Date: 3/28/96

Conditions of approval, if any: Fax'd copy to Lea I&E... HCE in mail.

Title 18 U.S.C. Section 1001, makes it a crime for any person knowingly and willfully to make in any department or agency of the United States any false, fictitious or fraudulent statements or representations or to any matter within its jurisdiction.

* See instruction on Reverse Side