

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION

P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-33531

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

V-4297

7. Lease Name or Unit Agreement Name

Coriander AOC State

8. Well No.

1

9. Pool name or Wildcat

Red Tank Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

YATES PETROLEUM CORPORATION

3. Address of Operator

105 South 4th St., Artesia, NM 88210

4. Well Location

Unit Letter A : 330 Feet From The North Line and 330 Feet From The East Line

Section 1

Township 23S

Range 32E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3744' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Spud, resume drilling, surface csg and cement ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spudded a 26" hole with rat hole machine at 11:30 AM 8-27-96. Set 40' of 20" conductor pipe. Cemented to surface. NOTE: Notified Bonnie w/OCD-Hobbs. Resumed drilling a 14-3/4" hole with rotary tools at 12:30 AM 8-25-96. NOTE: Notified OCD-Hobbs answering service.

TD 1150'. Reached TD at 1:50 PM 8-26-96. Ran 25 joints of 11-3/4" 42# H-40 8rd ST&C (1156.60') of casing set at 1150'. 1-Texas Pattern notched guide shoe set at 1150'. Insert float set at 1103'. Cemented with 500 sacks Premium Plus Hallibuton Lite, 1/4#/sack flocele, 5#/sack gilsonite and 2% CaCl2 (yield 1.99, weight 12.4). Tailed in with 200 sacks Halliburton Premium C and 2% CaCl2 (yield 1.32, weight 14.8). PD 12:30 AM 8-27-96. Bumped plug to 540 psi, OK. WOC. Nippled up and tested to 1000# for 30 minutes, OK. Drilled out at 7:00 PM 8-27-96. WOC 18 hours and 30 minutes. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Rusty Klein

TITLE

Operations Technician

DATE

Aug. 29, 1996

TYPE OR PRINT NAME

Rusty Klein

TELEPHONE NO. 505/748-1471

(This space for State Use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: