State of New Mexico

Form C-103

Submit 3 Copies , Minerals and Natural Resources Department Revised 1-1-89 to Appropriate District Office OIL CONSERVATION DIVISION DISTRICT WELL API NO. P.O. Box 1980, Hobbs, NM 88240 P.O. Box 2088 30-025-33574 Santa Fe. New Mexico 87504-2088 DISTRICT II 5. Indicate Type of Lease P.O. Drawer DD, Artesia, NM 88210 FEE STATE X DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. V-4297 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: MET X Coriander AOC State WELL OTHER 2. Name of Operator 8. Well No. YATES PETROLEUM CORPORATION 9. Pool name or Wildcat 3. Address of Operator 105 South 4th St., Artesia, NM 88210 Red Tank Bone Springs 4. Well Location ___ Line and 330 East Unit Letter H : 1650 Feet From The North Line Feet From The 23S Range 32E **NMPM** Lea County Township Section 10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3731' GR Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 11. SUBSEQUENT REPORT OF: **NOTICE OF INTENTION TO:** ALTERING CASING REMEDIAL WORK PLUG AND ABANDON PERFORM REMEDIAL WORK PLUG AND ABANDONMENT COMMENCE DRILLING OPNS. **CHANGE PLANS** TEMPORARILY ABANDON CASING TEST AND CEMENT JOB PULL OR ALTER CASING OTHER: Spud, surface casing & cement OTHER: 12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed Spudded a 22" hole with rat hole machine at 9:30 AM 9-30-96. Set 40' of 16" conductor pipe. Cemented to surface. NOTE: Notified Bonnie w/OCD-Hobbs of spud. Resumed drilling a 14-3/4" hole with rotary tools at 11:00 PM 9-30-96. TD 1154'. Reached TD at 3:15 AM 10-2-96. Ran 26 joints of 11-3/4" 42# H-40 8rd ST&C (1156.67') of casing set at 1153'. 1-Texas Pattern notched guide shoe set at 1153'. Insert float set at 1109'. Cemented with 450 sacks Class C, 6% gel, 3% CaCl2 & 1/4#/sack celloflake (yield 1.93, weight 12.6). Tailed in with 250 sacks "C" and 2% CaCl2 (yield 1.34, weight 14.8). PD 12:00 Noon 10-2-96. Bumped plug to 800 psi, OK. Circulated 245 sacks. WOC. Nippled up and tested to 1000# for 30 minutes, OK. Drilled out at 12:00 AM 10-3-96. WOC 12 hours. Reduced hole to 11". Resumed drilling.

I hereby certify that the information above is true, and complete to the best of my knowledge and belief. Operations Technician DATE Oct. 11, 1996 SIONATURE . Rusty Klein TELEPHONE NO. 505/748-1471 TYPE OR PRINT NAME (This space for State Use) ORIGINAL SIGNED BY GAST WINK DATE

CONDITIONS OF APPROVAL, IF ANY:

FIELD DEP. H

APPROVED BY -