Form 3160-5 (June 1990)

## **UNITED STATES** DEPARTMENT OF THE INTERIOR

N.M. Oil Cons. Division

P.O. Box 1980

FORM APPROVED
Budget Bureau No. 1004-0135 Expires: March 31, 1993

BUREAU OF LAND MANAGEMENT  SUNDRY NOTICES AND REPORTS ON WELLS  Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.		5. Lease Designation and Serial No.
		NM-88164
		6. If Indian, Allottee or Tribe Name
	III or to deepen or reentry to a different reservoir.  R PERMIT—" for such proposals	
USE AFFLICATION FOR	TENNIT - 101 Such proposals	
SUBMIT IN TRIPLICATE		7. If Unit or CA, Agreement Designation
		, , , u · ·
I. Type of Well		
X Oil Gas Well Other		8. Well Name and No.
2. Name of Operator	(505) 710 7171)	Parsley ARA Federal #1
YATES PETROLEUM CORPORATION	(505) 748–1471)	9. API Well No.
3. Address and Telephone No.		30-025-33863
105 South 4th St., Artesia, NM 88210  4. Location of Well (Footage, Sec., T., R., M., or Survey Description)		10. Field and Pool, or Exploratory Area
760' FSL & 990' FEL of Section 26-T23S-R32E (Unit P, SESE)		Wildcat Bone Spring
760. FSL & 990. FEL of Section	on 26-T23S-R32E (Unit P, SESE)	11. County or Parish, State
		Lea Co., NM
12. CHECK APPROPRIATE BOX(	s) TO INDICATE NATURE OF NOTICE, REPOR	RT, OR OTHER DATA
TYPE OF SUBMISSION	TYPE OF ACTION	
Notice of Intent	Abandonment	Change of Plans
	Recompletion	New Construction
Subsequent Report	Plugging Back	Non-Routine Fracturing
• •	Casing Repair	Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
	X Other Resume drilling,	Dispose Water
·	surface casing & cement	(Note: Report results of multiple completion on Well
13. Describe Proposed or Completed Operations (Clearly state a	l pertinent details, and give pertinent dates, including estimated date of starting	Completion or Recompletion Report and Log form.) g any proposed work. If well is directionally drilled,
	cal depths for all markers and zones pertinent to this work.)*	
Resumed drilling a 14-3/4" hole with rotary tools at 10:45 PM 3-26-97.		
TD 630'. Reached TD at 12:30 AM 3-27-97. Ran 15 joints of 11-3/4" 42# H-40 (633.46')		
of casing set at 630'. 1-Texas Pattern notched guide shoe set at 630'. Insert float set		
at 590'. Cemented with 200 sacks Thixad (12%) Class C, 8#/sack gilsonite, 1/4#/sack		
celloflake and 2% CaCl2 (yield 1.69, weight 14.1) and 200 sacks BJ Lite "C", 5#/sack gil-		
sonite, 1/4#/sack celloflake and 3% CaCl2 (yield 1.90, weight 12.7). Tailed in with		
	% CaCl2 (yield 1.33, weight 12.7). PI	
	Circulated 187 sacks to pit. WOC. No	
to 1000 psi for 30 minutes, 0	K. Drilled out at 11:30 AM 3-28-97.	WOC 18 hours. Reduced
hole to 11". Resumed drilling	ye intelliculate. Earl intelligible of home and provincing from a start to the constitution of the production of the constitution of the constitut	- mark #***
	ACCEPTED FOR DECORD	RECEIVED
		ACD TO A TO
·		
	acsi i	1.2
	grant per company of the control of	ROSWELL, NM
14. I hereby certify that the foregoing is true and correct		
14. I hereby certify that the foregoing is the and correct	Onematiana Washindadan	
Signed / Usley / flen	Tide Operations Technician	Date <u>April 2, 1997</u>
(This space for Federal or State office use)		
Approved by	Title	Date
Approved by		· · · · · · · · · · · · · · · · · · ·