

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

N.M. Oil Cons  
P. 1980  
Hobbs, NM 88241

FORM APPROVED  
Budget Bureau No. 1004-0135  
Expires: March 31, 1993

**SUNDRY NOTICES AND REPORTS ON WELLS**  
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir.  
Use "APPLICATION FOR PERMIT-" for such proposals

**SUBMIT IN TRIPLICATE**

1. Type of Well  
☒ Oil Well ☐ Gas Well ☐ Other

2. Name of Operator  
John H. Hendrix Corporation

3. Address and Telephone No.  
P. O. Box 3040, Midland, TX 79702-3040 (915) 684-6631

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)  
1980' FNL & 480' FEL, Unit H, Sec. 15, T22S, R37E

5. Lease Designation and Serial No.  
NMLC064427

6. If Indian, Allottee or Tribe Name

7. If Unit or CA, Agreement Designation

8. Well Name and No. 15 #5  
Elliott B No. 3

9. API Well No.  
30-025-34120

10. Field and Pool, or Exploratory Area  
Wantz Abo (62700)

11. County or Parish, State  
Lea County, NM

12. CHECK APPROPRIATE BOX(s) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION

- ☐ Notice of Intent  
☒ Subsequent Report  
☐ Final Abandonment Notice

TYPE OF ACTION

- ☐ Abandonment  
☐ Recompletion  
☐ Plugging Back  
☐ Casing Repair  
☐ Altering Casing  
☒ Other Run & cement csg.  
☐ Change of Plans  
☐ New Construction  
☐ Non-Routine Fracturing  
☐ Water Shut-Off  
☐ Conversion to Injection  
☐ Dispose Water

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11/9/97 Reached TD of 7500'. Ran 5-1/2" OD 15.5#/ft. J-55 csg. set at 7494'. DV tool @ 4484'.

11/10/97 Cemented 1st stage w/ 534 sx. 50/50 Poz/C. Did not circ. 1st stage. Cemented 2nd stage w/ 552 sx. Class "H" + 16% gel, tailed in w/ 502 sx. Class "C". Circ. 217 sx. to surface.

11/25/97 Drilled cement & DV tool at 4484'. Circ. hole clean & tested csg. to 2000 psig. OK. Drilled cement 7345 to 4477' RU Schlumberger and ran compensated neutron, GR CCL fr. 7436 to 2200'. GR to surface. Shut in waiting on BLM approval.

RECEIVED  
BUREAU OF LAND MGMT.  
HOBBS, NEW MEXICO  
JAN - 7 P 4: 05

14. I hereby certify that the foregoing is true and correct.

Signed Ronnie A. Mott Title Vice President

Date 01/06/98

(This space for Federal or State office use)

Approved by  
Conditions of approval, if any:

Title

Date