

+Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C 103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

P.O. Drawer DD, Artesia, NM 88210

DISTRICT TII
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO.	30-025-34877
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	
7. Lease Name or Unit Agreement Name	State 'A' A/C 1
8. Well No.	129
9. Pool name or Wildcat	Langlie Mattix 7 Rvrs-Q-Grayburg {37240}

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE APPLICATION FOR PERMIT (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:	Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> OTHER
2. Name of Operator	Raptor Resources, Inc.
3. Address of Operator	901 Rio Grande, Austin, TX 78701
4. Well Location	Unit Letter <u>C</u> <u>660</u> Feet From The <u>North</u> Line and <u>2130</u> Feet From The <u>West</u> Line Section <u>14</u> Township <u>23S</u> Range <u>36E</u> NMPM <u>Lea</u> County

10. Elevaun (Show whether DF, RKB, RT, GR, etc.)	3420
--	------

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER <input checked="" type="checkbox"/> Spud & set Surface Casing

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)SEE RULE 1103.

Spud 12 1/4" hole @ 1:15 pm on 3/24/00. Drill 12 1/4" hole to a depth of 610'. GIH W/ 14 jts 8 5/8" 24# casing set @ 610'. Lead cement 140 sx Class 'C' + 2% CaCl + 10% Bentonite gel. Tail cement 100 sx Class 'C' + 2% CaCl. Circulate 25 sx to surface. Plug down @ 1:15 am on 3/25/00. WOC. Will continue drilling 7 7/8" hole to total depth.

12. I hereby certify that the information above is true and complete to the best of my knowledge and belief.	
SIGNATURE <u>Bill R. Keathly</u>	TITLE <u>Regulatory Agent for Raptor</u> DATE <u>3-30-00</u>
TYPE OR PRINT NAME <u>Bill R. Keathly</u>	TELEPHONE NO. <u>915-697-1609</u>

(this space for State Use)

APPROVED BY <u>[Signature]</u>	TITLE <u></u>	DATE <u></u>
CONITIONS OF APPROVAL, IF ANY:		

