

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	
T. Salt	
B. Salt	
T. Yates	
T. 7 Rivers	
T. Queen	
T. Grayburg	4030'
T. San Andres	4885'
T. Glorieta	5104'
T. Paddock	5415'
T. Blinebry	5732'
T. Tubb	5840'
T. Drinkard	6330'
T. Abo	6584'
T. Wolfcamp	
T. Penn	
T. Cisco (Bough C)	

T. Canyon _____
T. Strawn _____
T. Atoka _____
T. Miss _____
T. Devonian _____
T. Silurian (Fusselman) _____ 7235'
T. Montoya _____ 7524'
T. Simpson _____
T. McKee _____
T. Ellenburger _____
T. Gr. Wash _____
T. Delaware Sand _____
T. Bone Springs _____
T. _____
T. _____
T. _____
T. _____

T. Ojo Alamo _____
T. Kirtland-Fruitland _____
T. Pictured Cliffs _____
T. Cliff House _____
T. Menefee _____
T. Point Lookout _____
T. Mancos _____
T. Gallup _____
Base Greenhorn _____
T. Dakota _____
T. Morrison _____
T. Todilto _____
T. Entrada _____
T. Wingate _____
T. Chinle _____
T. Permian _____
T. Penn "A" _____

T. Penn. "B" _____
T. Penn. "C" _____
T. Penn. "D" _____
T. Leadville _____
T. Madison _____
T. Elbert _____
T. McCracken _____
T. Ignacio Otzte _____
T. Granite _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____
T. _____

OIL OR GAS SANDS OR ZONES

No. 1, from...5400'.....to.....5620'.....

No. 3, from.....6330' ...to.....6520'

No. 2, from 5732' to.... 5740'.....

No. 4, from ...6920' ...to.....6970'

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from..... to..... feet.....

No. 2, from to feet.
No. 3, from to feet.

No. 3, from to feet.
..... to feet.

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology
0	2440	2440	Annhydrites & Red bed
2440	2760	220	Annhydrites & Shale
2760	3140	380	Annhydrites & Dolomite
3140	3650	410	Dolomite
3650	3700	50	Sand
3700	5030	1330	Dolomite & Limestone
5030	5140	110	Dolomite
5140	5160	20	Sand
5160	6480	1320	Dolomite
6480	7230	750	Dolomite & Limestone
7230	7500	270	Chert & Dolomite
7500	7630	130	Dolomite

From	To	Thickness In Feet	Lithology