

8. Auxiliary Well Control and Monitoring Equipment:

- A. A kelly cock will be kept in the drill string at all times.
- B. A full opening drill pipe stabbing valve (inside BOP) with proper drill pipe connections will be on the rig floor at all times.

9. Testing, Logging and Coring Program:

A Mudlogging unit will be on location from top of Delaware formation to TD. Mudlogging unit will be employed from approximately 4920' (Top of Delaware) to 9000' (Total Depth).

If indicated, AIT-GR, CNL-LDT-GR logs and Caliper logs will be run at TD. The Gamma Ray AIT will be run from TD back to the intermediate casing. The Gamma Ray Compensated Neutron Log will be run from TD back to surface. If indicated, Echo may elect to run rotary sidewall cores from selected intervals from approximately 4920' to 9000' dependent upon logging results.

10. Abnormal Conditions, Pressures, Temperatures and Potential Hazards:

No abnormal pressures or temperatures are anticipated. Anticipated bottomhole pressure is 3600# PSI.

Loss of circulation is possible in the Delaware section of the hole, however, no major loss circulation zones have been reported in offsetting wells.

Multiple wells have been drilled and completed in the immediate area. To date, Hydrogen Sulfide has not been encountered. However, if Hydrogen Sulfide is encountered, a Hydrogen Sulfide training and appropriate breathing apparatus is located on site. If necessary, the well can be shut in utilizing the blow out preventer and other equipment to prevent the migration of Hydrogen Sulfide to the surface.