

APPLICATION TO DRILL

CONCHO RESOURCES, INC..
TOMCAT "21" FEDERAL # 8
UNIT "I" SECTION 21
T23S-R32E LEA CO. NM

In response to questions asked under Section II of Bulletin NTL-6 the following information on the above well is provided for your consideration.

1. Location: 1980' FSL & 660' FWL SEC. 21 T23S-R32E

2. Elevation above Sea Level: 3673' GR.

3. Geologic name of surface formation: Quaternary Aeolian Deposits.

4. Drilling tools and associated equipment: Conventional rotary drilling rig using drilling mud as a circulating medium for solids removal from hole.

5. Proposed drilling depth: 9100'

6. Estimated tops of geological markers:

Lamar	4820'	Brushy Canyon	7359'
Bell Canyon	4850'	Bone Spring	8650'
Manzanita	5900'		

7. Possible mineral bearing formations:

Delaware	Oil
Bone Spring	Oil

8. Casing program:

Hole size	Interval	OD of casing	Weight	Thread	Collar	Grade
25"	0-40	20"	NA	NA	NA	Conductor
17½"	0-650' 1200'	13 5/8"	48	8-R	ST&C	H-40
11"	0-4900'	8 5/8"	32#	8-R	LT&C	K-55 S-30
7 8/7"	0-9100'	5½"	15.5# 17#	8-R	LT&C	K-55